



United States
ENVIRONMENTAL PROTECTION AGENCY

Washington, D.C. 20460

ENERGY STAR Roof Product Partner
Unit Shipment Data
Office of Atmospheric Programs

NAME OF MANUFACTURER: _____

DATE OF SUBMISSION: _____

SUBMITTED BY (NAME): _____

PLEASE LIST ANY UNAFFILIATED PRIVATE LABELERS THAT REBRAND YOUR PRODUCTS: _____

Below, only report shipments to consumers or retailers. Do not include business to business shipments (shipments to unaffiliated private labelers). If you ONLY ship to private labelers, indicate zero shipments and list private labelers selling in the U.S. marketplace on the line above.

Reporting Period: CALENDAR YEAR 2008 (JAN. TO DEC.)

| Roof Product Type | ENERGY STAR® U.S. Unit Shipments to Consumers or Retailers (REQUIRED) | Units | Total U.S. Unit Shipments to Consumers or Retailers (ENERGY STAR + Non-ENERGY STAR) (REQUESTED) | Units |
|---|--|-------------|---|-------------|
| Built-Up-Roof (BUR) ¹ | | Square Feet | | Square Feet |
| Coating ² | | Gallons | | Gallons |
| Metal ³ | | Square Feet | | Square Feet |
| Modified Bitumen ⁴ | | Square Feet | | Square Feet |
| Single-Ply ⁵ | | Square Feet | | Square Feet |
| Shingles ⁶ | | Square Feet | | Square Feet |
| Spray Polyurethane Foam (SPF) Roof System ^{7#} | | Gallons | | Gallons |
| Tile ⁸ | | Square Feet | | Square Feet |
| Total Gallons | 0 | | 0 | |
| Total Square Feet | 0 | | 0 | |

[#]For SPF - Data on the coating (i.e., not the foam itself).

*Unit Shipments in square footage or gallons, depending upon product, for roofing products.

Submission Deadline: February 27, 2009

Deadline to Avoid Partnership Termination: March 31, 2009

***Do not provide duplicate data to both SPRI and ICF**

SPRI members may submit data to:

Michael Egart
megart@associationresearch.com
Fax: (240) 268-1267

Please submit by mail, email, or fax to:

Elliott Rector
ICF International
1725 Eye Street, NW
Suite 1000
Washington, DC 20006
unitshipmentdata@icfi.com
Fax: (202) 862-1144

DEFINITIONS

¹ Built-Up-Roof (BUR): Traditional hot asphalt or coal tar built-up roofing membrane assembly consists of alternating layers of felts, fabrics, or mats saturated with bitumen during manufacture, assembled in place, and adhered with applied layers of hot bitumen. Surfacing for the hot BUR can be aggregate embedded in hot asphalt; mineral-surface cap sheets; modified bitumen cap sheets; or smooth-surface applications or coatings.

² Roof Coating: A material typically applied in the liquid state to the roof surface at the time of construction or at a later time as a retrofit measure. Roof coatings may be bituminous, polymeric, or polymer modified. Bituminous roof coatings are formulated using bitumen. Polymeric roof coatings are formulated using a variety of synthetic resins such as acrylic, neoprene, styrene butadiene, urethane, polyvinyl acetate, and others. Polymer modified roof coatings are manufactured by combining a portion of the polymeric technology with bitumen technology.

³ Metal: Metal roofing systems are divided into two categories, architectural and structural. Architectural metal roofs usually require a slope of at least 3:12. Structural metal roofs can be used on roofs with slopes as low as 1/4:12. Steel and aluminum sheets are commonly used to fabricate metal roof panels. Steel requires a corrosion resistant metal coating such as zinc, aluminum, alloys of zinc-aluminum, or tin. Metallic coated steel includes galvanized steel, aluminized steel, zinc-aluminum-coated steel and terne-coated steel. Metallic coated steels and Aluminum are also painted to provide additional corrosion protection, as well as color.

⁴ Modified Bitumen: Roll roofing products consisting of asphalt, reinforcing layers, and in some cases, surfacing. During manufacture, a polymer (APP, or atactic polypropylene, and SBS, or styrene butadiene styrene, are the most common) is added to the bitumen while heating, which "modifies," or changes, its properties.

⁵ Single-Ply Membrane: Flexible manufactured sheet of compounded synthetic materials. Single-ply membranes include EPDM (ethylene, propylene, diene monomer), Neoprene (chloroprene rubber), PVC (polyvinyl chloride polymers), CSPE (chlorosulfonated polyethylene, also known as Hypalon), CPE (chlorinated polyethylene), PIB (polyisobutylene), NBP (nitrite alloy membranes compounded from butadiene-acrylonitrile copolymers), TPO (thermoplastic polyolefin), and others.

⁶ Composite Shingle: Composed of a base material, either organic felt or glass fiber mat; asphalt; and surfacing material, generally in the form of mineral granules.

⁷ Spray Polyurethane Foam Roof System: A fully adhered system that consists of a rigid closed-cell sprayed-in-place polyurethane foam insulation and a protective roof coating. Typical coatings include acrylic, silicon, or urethane elastomers.

⁸ Roof Tile: May be composed of clay, concrete, fiber-cement, or synthetic materials. A variety of tile profiles, styles, finishes, and colors are available.

EPA plans to use the data only for program evaluations. EPA will release this information only as aggregated data and only to the extent required by law.

The public reporting and recordkeeping burden for this collection of information is estimated to average 6.69 hours per response. Send comments on the Agency's need for this information, the accuracy of the provided burden estimates, and any suggested methods for minimizing respondent burden, including through the use of automated collection techniques to the Director, Collection Strategies Division, U.S. Environmental Protection Agency (2822T), 1200 Pennsylvania Ave., NW, Washington, D.C. 20460. Include the OMB control number in any correspondence. Do not send the completed form to this address.