



ENERGY STAR CERTIFIED

# Uninterruptible Power Supplies

## APC by Schneider Electric - Back UPS PRO BN 1500VA 10 Outlets 2 USB Charging Ports AVR LCD interface : BN1500M2

### Specifications

<b>ENERGY STAR Unique ID:</b>	2333482
<b>Brand Name:</b>	APC by Schneider Electric
<b>Model Name:</b>	Back UPS PRO BN 1500VA 10 Outlets 2 USB Charging Ports AVR LCD interface
<b>Model Number:</b>	BN1500M2
<b>Power Conversion Mechanism:</b>	Static
<b>Minimum Configuration Tested Model Number:</b>	BN1500M2
<b>Active Output Power Rating Minimum Configuration (W):</b>	900
<b>Apparent Output Power Rating Minimum Configuration (VA):</b>	1500
<b>Topology (ac):</b>	Line Interactive
<b>Topology and Product Type Combined:</b>	ac Line Interactive (VI)
<b>Application:</b>	Consumer
<b>Rated Input Voltage (V rms):</b>	120-120
<b>Rated Input Frequency (Hz):</b>	60-60
<b>Rated Output Voltage (V):</b>	120-120
<b>Rated Output Frequency (Hz):</b>	60-60
<b>Rack Mountable:</b>	No
<b>Height (mm):</b>	260
<b>Width (mm):</b>	100
<b>Depth (mm):</b>	368
<b>Total Number of Outlets:</b>	10
<b>Number of Battery Backup and Surge Protected Outlets:</b>	6
<b>Number of Surge Protected Only Outlets:</b>	4
<b>Normal Mode(s) Input Dependency Characteristic (ac):</b>	Voltage and Frequency Dependent
<b>Modular UPS:</b>	No
<b>Number of Normal Modes:</b>	Single-normal-mode
<b>Default Normal Mode (ac):</b>	Voltage and Frequency Dependent
<b>Test Input Voltage (V rms):</b>	120

<b>Test Input Frequency (Hz):</b>	60
<b>Test Output Voltage (V):</b>	120
<b>Test Output Frequency (Hz):</b>	60
<b>Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):</b>	3.064
<b>Efficiency at 25% Load Min Config Lowest Dependency (ac):</b>	98.5
<b>Efficiency at 50% Load Min Config Lowest Dependency (ac):</b>	99.0
<b>Efficiency at 75% Load Min Config Lowest Dependency (ac):</b>	99.1
<b>Efficiency at 100% Load Min Config Lowest Dependency (ac):</b>	99.1
<b>Weighted Efficiency Calc Min Config Lowest Dependency:</b>	99.0
<b>Efficiency (%):</b>	99
<b>Modular UPS Module Tested Model Number:</b>	N/A
<b>Energy Storage Mechanism:</b>	Battery
<b>Energy Storage System Technology:</b>	Valve Regulated Lead-acid Battery
<b>Energy Storage System Configuration:</b>	Integral
<b>Energy Storage System Removable to Another Room:</b>	No
<b>Energy Storage System Runtime at 100% Load (min.):</b>	3
<b>Energy Storage System Runtime at 50% Load (min.):</b>	11
<b>Energy Storage System Warranty (yrs):</b>	3
<b>Energy Storage System Information URL:</b>	<a href="http://www.apc.com/shop/us/en/products/P-APCRBC161">http://www.apc.com/shop/us/en/products/P-APCRBC161</a>
<b>Battery Recycling URL:</b>	<a href="http://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp">http://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp</a>
<b>Network Connections Available:</b>	USB Port
<b>Communication Protocols:</b>	Other
<b>Communication Protocol Other:</b>	USB Power Summary
<b>Manufacturer Take Back Program:</b>	Yes
<b>Manufacturer Take Back Program URL:</b>	<a href="http://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp">http://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp</a>
<b>Model Web Page URL:</b>	<a href="http://www.apc.com/shop/us/en/products/P-BN1500M2">http://www.apc.com/shop/us/en/products/P-BN1500M2</a>
<b>Test Method Guidelines:</b>	<a href="http://www.apc.com/us/en/who-we-are/sustainability/">http://www.apc.com/us/en/who-we-are/sustainability/</a>
<b>Date Available on Market:</b>	2017-12-03
<b>Date Certified:</b>	2019-02-12
<b>Markets:</b>	United States
<b>ENERGY STAR Certified:</b>	Yes

## Additional Model Information

Back UPS PRO BN 1500VA 10 Outlets 2 USB Charging Ports AVR LCD interface Factory Serviced,BN1500M2W,; Std Exch Back UPS PRO BN 1500VA 10 Outlets 2 USB Charging Ports AVR LCD interface,BN1500M2Q,

<b>UPC Codes</b>	731304335375
------------------	--------------

**Captured On:**  
03/27/2023