



ENERGY STAR CERTIFIED

Uninterruptible Power Supplies

APC by Schneider Electric - APC Smart-UPS 1500VA LCD
RM 2U 120V with SmartConnAPC Smart-UPS 1500VA LCD
RM 2U 120V with SmartConnect Port : SMT1500RM2UC

Specifications

ENERGY STAR Unique ID:	2336960
Brand Name:	APC by Schneider Electric
Model Name:	APC Smart-UPS 1500VA LCD RM 2U 120V with SmartConnAPC Smart-UPS 1500VA LCD RM 2U 120V with SmartConnect Port
Model Number:	SMT1500RM2UC
Power Conversion Mechanism:	Static
Minimum Configuration Tested Model Number:	SMT1500RM2UC
Active Output Power Rating Minimum Configuration (W):	1000
Apparent Output Power Rating Minimum Configuration (VA):	1500
Topology (ac):	Line Interactive
Topology and Product Type Combined:	ac Line Interactive (VI)
Application:	Commercial
Rated Input Voltage (V rms):	110-125
Rated Input Frequency (Hz):	50-60
Rated Output Voltage (V):	110-125
Rated Output Frequency (Hz):	50-60
Rack Mountable:	Yes
Rack Mount Height (U):	2
Height (mm):	86
Width (mm):	432
Depth (mm):	477
Total Number of Outlets:	6
Number of Battery Backup and Surge Protected Outlets:	6
Number of Surge Protected Only Outlets:	0
Normal Mode(s) Input Dependency Characteristic (ac):	Voltage Independent
Modular UPS:	No
Number of Normal Modes:	Single-normal-mode
Default Normal Mode (ac):	Voltage Independent

Test Input Voltage (V rms):	125
Test Input Frequency (Hz):	60
Test Output Voltage (V):	125
Test Output Frequency (Hz):	60
Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):	3.56
Efficiency at 25% Load Min Config Lowest Dependency (ac):	98.4
Efficiency at 50% Load Min Config Lowest Dependency (ac):	98.9
Efficiency at 75% Load Min Config Lowest Dependency (ac):	98.9
Efficiency at 100% Load Min Config Lowest Dependency (ac):	98.8
Weighted Efficiency Calc Min Config Lowest Dependency:	98.9
Efficiency (%):	98.9
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Valve Regulated Lead-acid Battery
Energy Storage System Configuration:	Integral
Energy Storage System Removable to Another Room:	No
Energy Storage System Runtime at 100% Load (min.):	7
Energy Storage System Runtime at 50% Load (min.):	25
Energy Storage System Warranty (yrs):	2
Energy Storage System Information URL:	https://www.apc.com/shop/us/en/products/P-APCRBC133
Battery Recycling URL:	https://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp
Network Connections Available:	Serial Port,Ethernet,USB Port
Communication Protocols:	Other,Modbus TCP,Modbus RTU
Communication Protocol Other:	USB Power Summary, Simple Signalling, SmartConnect
Manufacturer Take Back Program:	Yes
Manufacturer Take Back Program URL:	https://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp
Model Web Page URL:	https://www.apc.com/shop/us/en/products/P-SMT1500RM2UC
Test Method Guidelines:	https://www.apc.com/us/en/who-we-are/sustainability/
Date Available on Market:	1575176400000
Date Certified:	1555387200000
Markets:	United States, Canada
ENERGY STAR Certified:	Yes

Additional Model Information

APC Smart-UPS 1500VA LCD RM 2U 120V with SmartConnect Port Factory Serviced,SMT1500RM2UCW,, Std Exch APC
Smart-UPS 1500VA LCD RM 2U 120V with SmartConnect Port,SMT1500RM2UCQ,

UPC Codes	731304322801
-----------	--------------

Captured On:
05/09/2024