

APC by Schneider Electric - Back UPS PRO BR 1500VA SineWave 10 Outlets 2 USB Charging Ports AVR LCD interface: BR1500MS2

Specifications ENERGY STAR Unique ID: 2365322 Brand Name: APC by Schneider Electric Model Name: Back UPS PRO BR 1500VA SineWave 10 Outlets 2 USB Charging Port AVR LCD Interface Model Number: BR1500MS2 Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: BR1500MS Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (W): Topology (ac): Line Interactive Topology (ac): Line Interactive (VI) Application: Consumer Rated Input Voltage (V rms): 120-120 Rated Input Voltage (V): 120-120 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: No Number of Surge Protected Only Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent		
Brand Name: APC by Schneider Electric Model Name: Back UPS PRO BR 1500VA SineWave 10 Outlets 2 USB Charging Port AVR LCD Interface Model Number: BR1500MS2 Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: BR1500MS Minimum Configuration Tested Model Number: BR1500MS Active Output Power Rating Minimum Configuration (W): Dough Power Rating Minimum Configuration (W): Dough Power Rating Minimum Configuration (VA): Dough P	Specifications	
Model Name: Back UPS PRO BR 1500VA SineWave 10 Outlets 2 USB Charging Port AVR LCD interface Model Number: BR1500MS2 Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: BR1500MS Active Output Power Rating Minimum Configuration (W): 900 Apparent Output Power Rating Minimum Configuration (VA): 1500 Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Consumer Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Only Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No Modular UPS: No Number of Normal Modes: Single-normal-mode	ENERGY STAR Unique ID:	2365322
AVR LCD interface Model Number: BR1500MS2 Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): 1500 Apparent Output Power Rating Minimum Configuration (VA): Line Interactive Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Consumer Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rated Output Frequency (Hz): 60-60 Rated Output Frequency (Hz): 100 Depth (mm): 260 Width (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No Modular UPS: No Number of Normal Modes: Single-normal-mode	Brand Name:	APC by Schneider Electric
Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: BR1500MS Active Output Power Rating Minimum Configuration (W): 900 Apparent Output Power Rating Minimum Configuration (VA): 1500 Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Consumer Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: 4 Number of Surge Protected Only Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No Modular UPS: No Number of Normal Modes: Single-normal-mode	Model Name:	Back UPS PRO BR 1500VA SineWave 10 Outlets 2 USB Charging Ports AVR LCD interface
Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Consumer Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Aumber of Surge Protected Only Outlets: No No No No Noundal UPS: No	Model Number:	BR1500MS2
Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Consumer Rated Input Voltage (V rms): Rated Input Frequency (Hz): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Frequency (Hz): Rated Output Frequency (Hz): Robert Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: No Number of Battery Backup and Surge Protected Outlets: Nomal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode	Power Conversion Mechanism:	Static
Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Consumer Rated Input Voltage (V rms): Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode		BR1500MS
Configuration (VA): Topology (ac): Line Interactive ac Line Interactive (VI) Application: Consumer Rated Input Voltage (V rms): Rated Input Frequency (Hz): Rated Output Frequency (Hz): Rated Output Frequency (Hz): Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: Number of Surge Protected Only Outlets: Voltage Independent Characteristic (ac): No Number of Normal Modes: No Number of Normal Modes: Single-normal-mode		900
Topology and Product Type Combined: Application: Rated Input Voltage (V rms): Rated Input Frequency (Hz): Rated Output Voltage (V): Rated Output Frequency (Hz): Rated Output Frequency (Hz): Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: No No Number of Surge Protected Only Outlets: No Modular UPS: No Number of Normal Modes: Single-normal-mode		1500
Application: Rated Input Voltage (V rms): Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: Number of Normal Modes: Single-normal-mode	Topology (ac):	Line Interactive
Rated Input Voltage (V rms): Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): Number of Normal Modes: Single-normal-mode	Topology and Product Type Combined:	ac Line Interactive (VI)
Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No Modular UPS: No Number of Normal Modes: Single-normal-mode	Application:	Consumer
Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No Modular UPS: No Number of Normal Modes: Single-normal-mode	Rated Input Voltage (V rms):	120-120
Rated Output Frequency (Hz): Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode	Rated Input Frequency (Hz):	60-60
Rack Mountable: Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Single-normal-mode	Rated Output Voltage (V):	120-120
Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode	Rated Output Frequency (Hz):	60-60
Width (mm): Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode	Rack Mountable:	No
Depth (mm): Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode	Height (mm):	260
Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode	Width (mm):	100
Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode	Depth (mm):	368
Protected Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode	Total Number of Outlets:	10
Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Voltage Independent No		6
Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode	Number of Surge Protected Only Outlets:	4
Number of Normal Modes: Single-normal-mode		Voltage Independent
	Modular UPS:	No
Default Normal Mode (ac): Voltage Independent	Number of Normal Modes:	Single-normal-mode
	Default Normal Mode (ac):	Voltage Independent
Test Input Voltage (V rms): 120	Test Input Voltage (V rms):	120

Test Input Frequency (Hz):	60
Test Output Voltage (V):	120
Test Output Frequency (Hz):	60
Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):	3.104
Efficiency at 25% Load Min Config Lowest Dependency (ac):	98.5
Efficiency at 50% Load Min Config Lowest Dependency (ac):	99.0
Efficiency at 75% Load Min Config Lowest Dependency (ac):	99.0
Efficiency at 100% Load Min Config Lowest Dependency (ac):	99.0
Weighted Efficiency Calc Min Config Lowest Dependency:	99.1
Efficiency (%):	99.1
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Valve Regulated Lead-acid Battery
Energy Storage System Configuration:	Integral
Energy Storage System Removable to Another Room:	No
Energy Storage System Runtime at 100% Load (min.):	4
Energy Storage System Runtime at 50% Load (min.):	14
Energy Storage System Warranty (yrs):	3
Energy Storage System Information URL:	http://www.apc.com/shop/us/en/products/P-APCRBC163
Battery Recycling URL:	http://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp
Network Connections Available:	USB Port
Communication Protocols:	Other
Communication Protocol Other:	USB Power Summary
Manufacturer Take Back Program:	Yes
Manufacturer Take Back Program URL:	http://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp
Model Web Page URL:	http://www.apc.com/shop/us/en/products/P-BR1500MS2
Test Method Guidelines:	http://www.apc.com/us/en/who-we-are/sustainability/
Date Available on Market:	1598760000000
Date Certified:	1598760000000
Markets:	United States, Canada
ENERGY STAR Certified:	Yes

Additional Model Information

Back UPS PRO 1500VA Sinewave 10 outlets 2 USB Charging ports AVR LCD Factory Serviced, BR1500MS2W,; Std Exch B ack UPS PRO 1500VA Sinewave 10 outlets 2 USB Charging ports AVR LCD, BR1500MS2Q,

UPC Codes 731304426103

Captured On: 04/26/2024