



# ENERGY STAR® Program Requirements Product Specification for Data Center Storage

## Eligibility Criteria Final Draft, Version 2.0

1 Following is the Final Draft, Version 2.0 ENERGY STAR Product Specification for Data Center Storage. A  
2 product shall meet all of the identified criteria if it is to earn the ENERGY STAR.

### 3 **1 DEFINITIONS**

#### 4 A. Product Types:

- 5 1) Storage Product: A fully-functional storage system that supplies data storage services to  
6 clients and devices attached directly or through a network. Components and subsystems that  
7 are an integral part of the storage product architecture (e.g., to provide internal  
8 communications between controllers and disks) are considered to be part of the storage  
9 product. In contrast, components that are normally associated with a storage environment at  
10 the data center level (e.g., devices required for operation of an external SAN) are not  
11 considered to be part of the storage product. A storage product may be composed of  
12 integrated storage controllers, storage devices, embedded network elements, software, and  
13 other devices. For purposes of this specification, a storage product is a unique configuration  
14 of one or more SKUs, sold and marketed to the end user as a Storage Product.
- 15 2) Storage Device: A collective term for disk drives (HDDs), solid state drives (SSDs), tapes  
16 cartridges, and any other mechanisms providing non-volatile data storage. This definition is  
17 specifically intended to exclude aggregating storage elements such as RAID array  
18 subsystems, robotic tape libraries, filers, and file servers. Also excluded are storage devices  
19 which are not directly accessible by end-user application programs and are instead employed  
20 as a form of internal cache.
- 21 3) Storage Controller: A device for handling storage request via a processor or sequencer  
22 programmed to autonomously process a substantial portion of I/O requests directed to  
23 storage devices (e.g., RAID controllers, filers).

#### 24 B. Storage Product Connectivity:

- 25 1) Direct-attached Storage (DAS): One or more dedicated storage devices that are physically  
26 connected to one or more servers.
- 27 2) Network Attached Storage (NAS): One or more dedicated storage devices that connect to a  
28 network and provide file access services (File I/O) to remote computer systems.
- 29 3) Storage Area Network (SAN): A network whose primary purpose is the transfer of data  
30 between computer systems and storage products. A SAN consists of a communication  
31 infrastructure, which provides physical connections, and a management layer, which  
32 organizes the connections, storage controllers / devices, and computer systems so that data  
33 transfer is secure and robust. The term SAN is usually (but not necessarily) identified with  
34 block I/O services rather than file access services.

35

- 36 C. Capacity Optimizing Methods (COMs)<sup>1</sup>: The reduction of actual data stored on storage devices  
37 through a combination of hardware and / or software. Common COMs include:
- 38 1) Thin Provisioning: A technology that allocates the physical capacity of a volume or file system  
39 as applications write data, rather than allocating all the physical capacity at the time of  
40 provisioning.
- 41 2) Data Deduplication: The replacement of multiple copies of data – at variable levels of  
42 granularity – with references to a shared copy in order to save storage space and/or  
43 bandwidth.
- 44 3) Compression: The process of encoding data to reduce its size. For the purpose of this  
45 specification, only lossless compression (i.e., compression using a technique that preserves  
46 the entire content of the original data, and from which the original data can be reconstructed  
47 exactly) is recognized.
- 48 4) Delta Snapshots: A type of point-in-time copy that preserves the state of data at an instant in  
49 time by storing only those blocks that are different from an already existing full copy of the  
50 data.
- 51 D. Storage Taxonomy<sup>1</sup>: A categorization scheme for use in segmenting the data center storage  
52 market by end-use application and key product characteristics. The major categories of the  
53 taxonomy that are referenced in this document are as follows:
- 54 1) Disk Set Online Storage: Storage products that are intended to service a mixture of Random  
55 and Sequential I/O requests with a short response time. All data stored in Disk Set Online  
56 storage must be accessible MaxTTFD ≤ 80 ms, unless the storage product is in a Deep Idle  
57 state. Disk set Online storage is typically comprised of one or more HDDs and a storage  
58 controller and provides primary data storage to supplement a Computer Server's internal  
59 memory.
- 60 2) Disk Set Near-online Storage: Storage products that are intended to service a mixture of  
61 Random and Sequential I/O requests with a short to moderate response time. Disk Set Near-  
62 online storage products offer an asymmetrical response; a portion of data may be accessible  
63 MaxTTFD ≤ 80 milliseconds, while other data may be accessible MaxTTFD > 80  
64 milliseconds.
- 65 3) Removable and Virtual Media Library (RVML) Set Virtual Media Library: Storage products  
66 that are intended to service primarily Sequential I/O, with a short response time. The media in  
67 a Virtual Media Library (e.g., HDD, optical disk) is not designed to be physically removed from  
68 the system. All data stored in the Virtual Media Library must be assessable MaxTTFD ≤ 80  
69 ms, unless the storage product is in a Deep Idle state. Virtual Medial Libraries are intended  
70 primarily for moderate and long-term data storage.
- 71 4) RVML Set Removable Media Library: Storage products that are intended to service primarily  
72 Sequential I/O, with a moderate to long response time. The media (e.g., tape cartridge,  
73 optical disk) in a Removable Media Library is designed to be physically removed from the  
74 storage product. Removable Media Libraries are intended primarily for long term data  
75 archiving

---

<sup>1</sup> The ENERGY STAR storage taxonomy and COM references in this document are consistent with the terminology developed by the Storage Networking Industry Association Green Storage Initiative as defined in "SNIA Emerald™ Power Efficiency Measurement Specification" Version 4.0.0. Further detail may be found at [www.snia.org/green](http://www.snia.org/green).

76 5) Non-volatile Solid State (NVSS) Set Disk Access Storage: Storage products that are intended  
77 to service a mixture of Random and Sequential I/O requests with a short response time. All  
78 data stored in NVSS Set Disk Access Online storage must be accessible  $\text{MaxTTFD} \leq 80$  ms,  
79 unless the storage product is in a Deep Idle state. NVSS Set Disk Access Online storage is  
80 typically comprised of one or more SSDs and a storage controller and provides primary data  
81 storage to supplement a Computer Server's internal memory.

82 6) NVSS Set Memory Access Storage: Storage products that are intended to service a mixture  
83 of Random and Sequential I/O requests with a short response time. All data stored in NVSS  
84 Set Memory Access Online storage must be accessible  $\text{MaxTTFD} \leq 80$  ms, unless the  
85 storage product is in a Deep Idle state. NVSS Set Memory Access Online storage is typically  
86 comprised of one or more banks of Solid State Storage devices and a storage controller and  
87 provides primary data storage to supplement a Computer Server's internal memory.

88 E. Other Data Center Equipment:

89 1) Computer Server: A computer that provides services and manages networked resources for  
90 client devices (e.g., desktop computers, notebook computers, thin clients, wireless devices,  
91 PDAs, IP telephones, other computer servers and other network devices). A computer server  
92 is sold through enterprise channels for use in data centers and office/corporate environments.  
93 A computer server is primarily accessed via network connections, versus directly-connected  
94 user input devices such as a keyboard or mouse. For purposes of this specification, a product  
95 must meet all of the following criteria to be considered a computer server:

- 96 i) is marketed and sold as a Computer Server;
- 97 ii) is designed for and listed as supporting computer server operating systems (OS) and/or  
98 hypervisors;
- 99 iii) is targeted to run user-installed applications typically, but not exclusively, enterprise in  
100 nature;
- 101 iv) provides support for error-correcting code (ECC) and/or buffered memory (including both  
102 buffered DIMMs and buffered on board (BOB) configurations)
- 103 v) is packaged and sold with one or more ac-dc or dc-dc power supplies; and
- 104 vi) is designed such that all processors have access to shared system memory and are  
105 visible to a single OS or hypervisor.

106 2) Network Equipment: A device whose primary function is to provide data connectivity among  
107 an arbitrary combination of devices connected to its several ports. Data connectivity is  
108 achieved via the routing of data packets encapsulated according to Internet Protocol, Fibre  
109 Channel, InfiniBand or other standard protocol. Examples of network equipment commonly  
110 found in data centers are routers and switches.

111 3) Blade Storage: A storage product that is designed for use in a blade chassis. A blade storage  
112 product is dependent upon shared blade chassis resources (e.g., power supplies, cooling) for  
113 operation.

114 4) Cache: Temporary storage used to transparently store transitory data and which is not  
115 directly addressable by end-user applications. Primarily used for expediting access to or from  
116 (typically) slower devices.

117 F. Capacity: Capacity is reported in units of either binary bytes (1 MiB = 1,048,576 Byte) or decimal  
118 bytes (1 MB = 1,000,000 Byte).

119 1) Assigned Capacity: The amount of space on a system or data container which has been  
120 allotted to be written by an end user or application. (Note: For thin provisioning systems, an  
121 assigned capacity number represents a promise that that amount of space will be provided on  
122 demand; usable capacity is allocated as the container is written too. For fully-provisioned  
123 systems, usable capacity must be committed at the same time the container is allocated.)

- 124 2) Effective Capacity: The amount of data stored on a storage product, plus the amount of  
125 unused formatted capacity in the system.
- 126 3) Formatted (Usable) Capacity: The total amount of bytes available to be written after a storage  
127 product or storage device has been formatted for use (e.g., by an object store, file system or  
128 block services manager). Formatted capacity is less than or equal to raw capacity. It does not  
129 include areas set aside for system use, spares, RAID parity areas, checksum space, host- or  
130 file system-level remapping, "right sizing" of disks, disk labeling and so on. However,  
131 formatted capacity may include areas that are normally reserved – such as snapshot set-  
132 asides – if these areas may be configured for ordinary data storage.
- 133 4) Free Space: The amount of unused, formatted capacity as reported by the storage product.
- 134 5) Raw (Addressable) Capacity: The sum total amount of addressable capacity of the storage  
135 devices in a storage product. The raw capacity of a storage device is commonly understood  
136 to be the number of bytes available to be written via SCSI or equivalent protocol. It does not  
137 include unaddressable space, ECC (error correcting code) data, remap areas, inter-sector  
138 gaps, etc.

139 G. Operational States:

- 140 1) Active State: The state in which a storage product is processing external I/O requests.
- 141 2) Idle State: An operational state in which the storage product is capable of completing I/O  
142 transactions, but no active I/Os are requested or pending. The system may, however, be  
143 servicing self-initiated I/Os from background data protection and cleansing, and other  
144 operations not initiated by the user.
- 145 i) Ready Idle: The state in which a storage product is able to respond to arbitrary I/O  
146 requests within the MaxTTFD limits for its taxonomy category but is not receiving external  
147 I/O requests. The storage product may perform routine housekeeping tasks during Ready  
148 Idle, provided such operations do not compromise the product's ability to meet MaxTTFD  
149 requirements.
- 150 ii) Deep Idle: A state in which one or more storage product components or subsystems have  
151 been placed into a low-power state for purpose of conserving energy. A storage product  
152 in Deep Idle may not be able to respond to I/O requests within the MaxTTFD limits for its  
153 taxonomy category, and may need to perform a managed 'wake-up' function in order to  
154 return to a Ready Idle or Active State. Deep Idle capability must be a user-selected,  
155 optional feature of the storage product.

156 H. Power Supply Unit (PSU): A device that converts ac or dc input power to one or more dc power  
157 outputs for the purpose of powering a storage product. A storage PSU must be self-contained  
158 and physically separable from the system and must connect to the system via a removable or  
159 hard-wired electrical connection. Note: Storage PSUs may be Field Replaceable Units (FRUs),  
160 but in some cases may be further integrated with the storage product.

- 161 1) Ac-dc Power Supply: A PSU that converts line-voltage ac input power into one or more dc  
162 power outputs.
- 163 2) Dc-dc Power Supply: A PSU that converts line-voltage dc input power to one or more dc  
164 power outputs. For purposes of this specification, a dc-dc converter (also known as a voltage  
165 regulator) that is internal to a storage product and is used to convert a low voltage dc (e.g., 12  
166 V dc) into other dc power outputs for use by storage product components is not considered a  
167 dc-dc power supply.

- 168 3) Single-output Power Supply: A PSU that is designed to deliver the majority of its rated output  
169 power to one primary dc output. Single-output PSUs may offer one or more standby outputs  
170 that remain active whenever connected to an input power source. For purposes of this  
171 specification, the total rated power output from all additional PSU outputs that are not primary  
172 or standby outputs shall be less than or equal to 20 watts. PSUs that offer multiple outputs at  
173 the same voltage as the primary output are considered single-output PSUs unless those  
174 outputs (1) are generated from separate converters or have separate output rectification  
175 stages, or (2) have independent current limits.
- 176 4) Multi-output Power Supply: A PSU that is designed to deliver the majority of its rated output  
177 power to more than one primary dc output for the purpose of powering a storage product.  
178 Multi-output PSUs may offer one or more standby outputs that remain active whenever  
179 connected to an input power source. For purposes of this specification, the total rated power  
180 output from all additional PSU outputs that are not primary and standby outputs must be  
181 greater than or equal to 20 watts.
- 182 5) Redundant Power Supplies: Two or more PSUs that are configured to maintain uninterrupted  
183 output load in the event of failure of one PSU.
- 184 I. Product Family: A group of models/configurations that share a set of common attributes that are  
185 variations on a basic design.
- 186 1) Common Product Family Attributes: A set of features common to all models/configurations  
187 within a product family that constitute a common basic design. All models/configurations  
188 within a product family must share the following:
- 189 i) made by the same manufacturer;
  - 190 ii) be from the same model line or machine type;
  - 191 iii) utilize the same model of storage controller;
  - 192 iv) fall under the same taxonomy category; and
  - 193 v) contain equal or greater amount of cache than the corresponding certified configuration.
- 194 2) Optimal Configuration: A product configuration which is representative of a product's  
195 maximum peak energy efficiency performance (performance/watt) for a given workload type.  
196 This configuration represents all products certified within the family under the associated  
197 workload type specified. This configuration is provided by the manufacturer and may be  
198 optimized for the following workload types:
- 199 i) Transaction (Block I/O products only): A workload optimized for random I/O usage  
200 measured in I/O per second per watt;
  - 201 ii) Streaming (Block I/O products only): A workload optimized primarily for sequential I/O  
202 usage, measured in MiB per second per watt;
  - 203 iii) Composite (File I/O products only): A workload optimized for mixed I/O usage, measured  
204 in MiB per second per watt.
- 205 J. Other Definitions:
- 206 1) Scale-Up Storage: A storage product comprised of a discreet storage controller (with or  
207 without redundancy), which has a full view of all the storage devices in the storage product.  
208 Incremental storage capacity is added by the addition of storage devices under the control  
209 of the existing storage controller.

- 210 2) Scale-Out Storage: A storage product capable of being comprised of two or more discreet  
211 storage controllers (with or without redundancy), combined with an overall integration or  
212 aggregation function resulting in a single storage product view for attached servers. Each  
213 discreet storage controller often has a partial view to a partition of the overall system's  
214 storage devices, but this is not a fixed requirement. Incremental storage capacity is added  
215 by the addition of storage devices under the control of the existing storage controller(s)  
216 and/or addition of additional storage devices along with additional controller(s).
- 217 3) Field-replaceable Unit (FRU): A unit, or component of a system that is designed to be  
218 replaced "in the field;" i.e., without returning the system to a factory or repair depot. Field  
219 replaceable units may either be customer-replaceable, or their replacement may require  
220 trained service personnel.
- 221 4) High-availability (HA): The ability of a system to perform its function continuously (without  
222 interruption) for a significantly longer period of time than the reliabilities of its individual  
223 components would suggest. High availability is most often achieved through failure  
224 tolerance.
- 225 5) Maximum Time to First Data (MaxTTFD): The maximum time required to start receiving  
226 data from a storage product to satisfy a read request for arbitrary data.
- 227 6) RAS Features: An acronym for reliability, availability, and serviceability features. RAS is  
228 sometimes also expanded to RASM, which adds "Manageability" criteria. The three primary  
229 components of RAS as related to storage products are defined as follows:
- 230 i) Reliability Features: Features supporting a storage product's ability to perform its  
231 intended function without interruption due to component failures. Technologies applied to  
232 increase reliability include: component selection (MTBF), redundancy (both at a micro  
233 and macro levels), temperature and/or voltage de-rating, error detection and correction  
234 technologies.
- 235 ii) Availability Features: Features that support a storage product's ability to maximize normal  
236 operating time and minimize planned and unplanned down time.
- 237 iii) Serviceability Features: Features that support a storage product's ability to be serviced  
238 (e.g., hot-plugging).
- 239 iv) Advanced Data Recovery Capability: A collective term used in this specification to refer to  
240 error detection and correction features such as RAID, mirroring / grid technology, or other  
241 comparable advanced error detection and recovery systems
- 242 v) Non-disruptive Serviceability: Support for continued availability of data and response  
243 times during all FRU and service operations; including break/fix, code patches,  
244 software/firmware upgrades, configuration changes, data migrations, and system  
245 expansion.
- 246 7) Block I/O Loads:
- 247 i) Random Read: Any I/O load in which consecutively issued read requests do not specify  
248 adjacently addressed data. The term random I/O is commonly used to denote any I/O  
249 load that is not sequential, whether or not the distribution of data locations is indeed  
250 random.
- 251 ii) Random Write: Any I/O load whose consecutively issued write requests do not specify  
252 adjacently addressed data. The term random I/O is commonly used to denote any I/O  
253 load that is not sequential, whether or not the distribution of data locations is indeed  
254 random.
- 255 iii) Sequential Read: An I/O load consisting of consecutively issued read requests to  
256 adjacently addressed data.

- 257 iv) Sequential Write: An I/O load consisting of consecutively issued write requests to  
258 adjacently addressed data.
- 259 v) Hot Band: An I/O load consisting of a collection of read and write requests that models  
260 areas of higher frequency I/O activity over the addressed data.
- 261 8) File I/O Loads:
- 262 i) DATABASE: An I/O load that simulates an OLTP database Table and Log file scenario.
- 263 ii) Software (SW) Build: An I/O load that simulates a large software project compilation or  
264 build phase of an EDA workflow.
- 265 iii) Video Data Acquisition (VDA): An I/O load that simulates acquisition of data from a  
266 temporarily volatile source such as surveillance or big data ingestion.
- 267 iv) Virtual Desktop Infrastructure (VDI): An I/O load that simulates the workload generated by  
268 a hypervisor to support a heavy steady-state knowledge worker workload.
- 269 9) Response Time: The time required for the UUT to complete an I/O request.
- 270 10) Unit Under Test (UUT): The storage product being tested.

## 271 **2 CERTIFYING PRODUCTS**

### 272 **2.1 Included Products**

- 273 2.1.1 Products that meet all of the following conditions are eligible for ENERGY STAR certification,  
274 with the exception of products listed in Section 2.2:
- 275 i. meet the definition of a Storage Product provided in Section 1 of this document;
- 276 ii. are comprised of one or more SKUs and be able to be purchased in a single order from a  
277 storage product vendor;
- 278 iii. are characterized within the Disk Set Online categories 2, 3, or 4 and NVSS Set Disk Access  
279 categories Online 2, 3 or 4 with the following additional criteria;

280 **Note:** EPA has corrected the reference in Section 2.1.1.iii to capture Online 2, 3 and 4 NVSS Set Disk  
281 Access categories.

- 282 a) contain a controller with advanced data recovery capability
- 283 b) support Block I/O and/or File I/O storage functions; and
- 284 c) implement scale-up or scale-out storage.

### 285 **2.2 Excluded Products**

- 286 2.2.1 Products that are covered under other ENERGY STAR product specifications are not eligible  
287 for certification under the ENERGY STAR Data Center Storage specification. The full list of  
288 specifications currently in effect can be found at [www.energystar.gov/specifications](http://www.energystar.gov/specifications).
- 289 2.2.2 The following products are specifically excluded from certification under this specification:
- 290 i. Personal / Portable Data Storage Products;
- 291 ii. Computer Servers;
- 292 iii. Blade Storage Products;
- 293 iv. Direct Attached Storage Products

- v. Storage Products capable of only object based storage;
- vi. Storage devices in the following categories of the taxonomy: Disk Set Near-Online, RVML Set Removable Media Library, RNML Set Virtual Media Library and NVSS Set Memory Access.

### 3 CERTIFICATION CRITERIA

#### 3.1 Significant Digits and Rounding

- 3.1.1 All calculations shall be carried out with directly measured (unrounded) values.
- 3.1.2 Unless otherwise specified, compliance with specification limits shall be evaluated using directly measured or calculated values without any benefit from rounding.
- 3.1.3 Directly measured or calculated values that are submitted for reporting on the ENERGY STAR website shall be rounded to the nearest significant digit as expressed in the corresponding specification limit.

#### 3.2 Power Supply Requirements

- 3.2.1 Power Supply Units (PSUs): PSUs used in storage products eligible under this specification shall meet the following requirements when tested using the *EPRl Generalized Internal Power Supply Efficiency Test Protocol, Rev. 6.7.1* (available at [https://www.plugloadsolutions.com/docs/collatrl/print/Generalized\\_Internal\\_Power\\_Supply\\_Efficiency\\_Test\\_Protocol\\_R6.7.1.pdf](https://www.plugloadsolutions.com/docs/collatrl/print/Generalized_Internal_Power_Supply_Efficiency_Test_Protocol_R6.7.1.pdf)).
- 3.2.2 Efficiency and Power Factor in Primary Embedded Equipment: Embedded PSUs that power primary components of the storage product, including controllers and drawers, must meet the requirements in Table 1 and Table 2.
  - i. Efficiency: A storage product PSU shall meet efficiency requirements as specified in **Error! Reference source not found..**

**Table 1: Efficiency Requirements for PSUs**

Power Supply Type	Rated Output Power	20% Load	50% Load	100% Load
Multi-output (Ac-Dc)	All Output Levels	88%	92%	88%
Single-output (Ac-Dc)	All Output Levels	90%	94%	91%

- ii. Power Factor: A storage product PSU shall meet power factor requirements as specified in Table 2.

**Table 2: Power Factor Requirements for PSUs**

PSU Type	Rated Output Power	20% Load	50% Load	100% Load
Single and Multi-Output PSU	All Output Levels	0.80	0.90	0.95

**Note:** EPA has updated the PSU Type references in Table 2 to reference Single and Multi-output PSUs to align with Table 1.

323 iii. Embedded PSUs that do not power primary components of the storage product are not  
 324 subject to PSU requirements.

325 **3.3 Energy Efficiency Active State Requirements for Block I/O Systems**

326 3.3.1 To certify for ENERGY STAR, each Optimal Configuration point submitted for a block I/O  
 327 storage product or storage product family must meet the following applicable active state  
 328 requirements in Table 3 for each workload type for which it is certified.  
 329

330 **Table 3: Active State Requirements for Block I/O Storage Products**

Workload Type	Specific Workload Test	Minimum Performance/Watt Ratio	Applicable Units of Ratio
Transaction	Hot Band	28.0	IOPS/watt
Streaming	Sequential Read	2.3	MiBS/watt
Streaming	Sequential Write	1.5	MiBS/watt

331  
 332 3.3.2 An Optimal Configuration point submitted for a streaming workload must meet either the  
 333 sequential read or sequential write requirement in Table 3 above but is not required to meet  
 334 that value for both workload tests. Both test values will be reported and displayed publicly  
 335 regardless of whether they meet the criteria in Table 3.

336 **3.4 Energy Efficiency Feature Requirements**

337 3.4.1 To certify for ENERGY STAR, a storage product must contain the following feature,  
 338 implemented as specified:

339 i. *Adaptive Active Cooling*: Primary components of a storage product must utilize adaptive  
 340 cooling technologies that reduce the energy consumed by the cooling technology in  
 341 proportion to the current cooling needs to the storage product. (e.g., reduction of variable  
 342 speed fan or blower speeds at lower ambient air temperature). This requirement is not  
 343 applicable to devices that employ passive cooling.

344 3.4.2 A storage product shall make available to the end user configurable / selectable features listed  
 345 in Table 4 in quantities greater than or equal to those listed in Table 5.  
 346

347 **Table 4: Recognized COM Features**

Feature	Verification Requirement
COM: Thin Provisioning	SNIA verification test
COM: Data Deduplication	SNIA verification test
COM: Compression	SNIA verification test
COM: Delta Snapshots	SNIA verification test

348  
 349  
 350 **Table 5: COM Requirements for Disk Set and NVSS Disk Set Access Online 2, 3 and 4 Systems**

Storage Product Category	Minimum number of COMs required to be made available
--------------------------	--

Online 2	1
Online 3	2
Online 4	3

351 **3.5 Information Reporting Requirements**

352 3.5.1 Active and Idle State Efficiency Disclosure: To certify for ENERGY STAR, all active and idle  
 353 state test results based on workload tests listed in Table 6 or Table 7 shall be reported:

354 **Table 6: Required Workload Tests for all Block I/O Configurations**

Workload Test
Hot Band
Random Read
Random Write
Sequential Read
Sequential Write
Ready Idle <sup>2</sup>

355 **Table 7: Required Workload Tests for all File I/O Configurations**

Workload Test
DATABASE
SW Build
VDA
VDI
Ready Idle <sup>3</sup>

356 3.5.2 Workload Weighting Requirements: The weighted percentages shown in Table 8 or Table 9  
 357 shall be used to calculate the appropriate Optimal Configuration point for a given storage  
 358 product.

359 **Table 8: Workload Weighting Requirements for all Block I/O Systems**

Workload Test	Transaction Optimization	Streaming Optimization
Hot Band	100%	0%
Sequential Read	0%	50%
Sequential Write	0%	50%
Ready Idle	0%	0%

360 **Example:** To optimize for a streaming workload, manufacturers should identify a system configuration  
 361 and storage device count where the weighted sum (per Table 8) of the Sequential Read and Sequential  
 362 Write results are maximized. The resulting storage device count should be used as the streaming  
 363 optimization point for ENERGY STAR testing and certification. The same weighting of the sums should  
 364 also be used for subsequent certification measurements.  
 365

<sup>2</sup> SNIA defined workload tests in Table 6, Table 7, and through the rest of this document can be found in the "SNIA Emerald™ Power Efficiency Measurement Specification" Version 4.0.0. Further detail may be found at [www.snia.org/green](http://www.snia.org/green).

**Note:** EPA has corrected a reference in the example above to reference Table 8 rather than Table 7. EPA has also removed an obsolete reference to flexible and mixed certification ranges as well as the column referencing capacity optimization in Table 8.

**Table 9: Workload Weighting Requirements for all File I/O Systems**

Workload Test	Transaction Optimization	Streaming Optimization	Composite Optimization
DATABASE	50%	0%	0%
SW Build	0%	0%	100%
VDA	0%	100%	0%
VDI	50%	0%	0%

3.5.3 Testing Data Requirements for all Scale-up Storage Products: The following test data is required for each configuration submitted for certification as ENERGY STAR:

- i. The manufacturer must choose a workload type for testing from 1.1.2.
- ii. The manufacturer must choose a single type of or combination of hard disk storage devices and solid state storage devices which result in the highest work/watt for that workload type. The amount of solid state storage devices in the tested configuration in a hybrid disk/solid state configuration cannot exceed 30% of the addressable storage being represented by solid state unless the product is testing with only solid state devices in which all devices in the configuration shall be solid state devices.
- iii. For the chosen workload type, physical data for all measurements listed in Table 6 or Table 7 shall be submitted for a manufacturer determined Optimal Configuration point Additionally:
- iv. To certify additional workload types, repeat the above starting at 3.5.3.i for a different workload.
- v. The following rules apply to all testing above:
  - (a) Verification testing of COM features (Table 4) specified by the storage product shall be executed at least once using storage devices of the vender's choice. Once verified there is no requirement to re-execute the COM verification testing procedure with different storage devices.

3.5.4 Testing Data Requirements for all Scale-out Storage Products: The following test data is required for each configuration submitted for certification as ENERGY STAR:

- i. All testing and data requirements of Sections 3.5.3 shall be followed.
- ii. When testing, the smallest marketed quantity of storage controllers / nodes shall be tested.
- iii. Additional systems with a larger quantity of storage controllers may be optionally submitted.

3.5.5 Data for display on the ENERGY STAR website shall be submitted for each ENERGY STAR certified storage product or storage product family.

- i. Whenever possible, Partners should also provide a hyperlink to a more detailed power calculator on their website that purchasers can use to understand power and performance data for specific configurations within the product family.

3.5.6 The following information will be displayed on the ENERGY STAR website:

- i. Product model name, model number, and SKU or other configuration identification number;
- ii. A list of important product characteristics, including;

- 402 (a) System configuration and tested I/O type;
  - 403 (b) Storage controller details (e.g. model name and number);
  - 404 (c) Software configuration and transfer protocols used in testing;
  - 405 (d) Storage controller power supply information;
  - 406 (e) Storage device drawer power supply information;
  - 407 (f) Storage devices used per optimization points;
  - 408 (g) Input power and environmental characteristics during testing;
  - 409 (h) System power optimization capabilities;
  - 410 (i) Inlet air temperature and power consumption reporting capabilities.
- 411 iii. A list of optimal configurations of certified product families; and disclosure of the time period
  - 412 used for data averaging.
  - 413 iv. A list of power management and other power saving features available and enabled by
  - 414 default;
  - 415 v. Specified thermal measurements conducted during testing;
  - 416 vi. For product families, a list of certified storage products within the family; and
  - 417 vii. Energy Efficiency Performance data (performance/watt) for required active and idle state test
  - 418 reporting specified in Table 10 or Table 11 below:

419 **Table 10: Active and Idle State Efficiency Block I/O Test Results Displayed**

Workload Test	Transaction Optimization	Streaming Optimization	Capacity Optimization
Hot Band	Yes	No	No
Random Read	Yes	No	No
Random Write	Yes	No	No
Sequential Read	No	Yes	No
Sequential Write	No	Yes	No
Ready Idle	Yes	Yes	Yes

421 **Table 11: Active and Idle State Efficiency File I/O Test Results Displayed**

Workload Test	Transaction Optimization	Streaming Optimization	Composite Optimization
DATABASE	Yes	No	No
SW Build	No	No	Yes
VDA	No	Yes	No
VDI	Yes	No	No
Ready Idle	Yes	Yes	Yes

423 3.5.7 The following test information shall be submitted as part of the certification process, but will not  
424 be displayed on the ENERGY STAR website:

425 i. Discrete power and performance data for all tested configurations;

### 426 3.6 Standard Performance Data Measurement and Output Requirements

427 3.6.1 Data Elements: Disk Set and NVSS Disk Set Access Online 3 and Online 4 storage products  
428 shall be capable of measuring and reporting the following data elements at the storage product  
429 level:

430 i. Input Power, in watts. Input power measurements must be reported with accuracy within  
431  $\pm 5\%$  of the actual value for measurements greater than 200 W, through the full range of  
432 operation. For measurements less than or equal to 200 W, the accuracy must be less than  
433 or equal to 10 W multiplied by the number of installed PSUs; and

434 ii. Inlet Air Temperature, in degrees Celsius, with accuracy of  $\pm 2^\circ\text{C}$ .

435 3.6.2 Reporting Implementation:

436 i. Data shall be made available in a published or user-accessible format that is readable by  
437 third-party, non-proprietary management systems;

438 ii. Data shall be made available to end users and third-party management systems over a  
439 standard network connection;

440 iii. Data shall be made available via embedded components or add-in devices that are  
441 packaged with the storage product (e.g., a service processor, embedded power or thermal  
442 meter or other out-of-band technology, or pre-installed OS);

443 iv. When an open and universally available data collection and reporting standard becomes  
444 available, manufacturers should incorporate the universal standard into their products.

445 v. Inlet air temperature data shall be reported for the controller chassis only.

446 3.6.3 Sampling Requirements:

447 i. *Input power*: Input power measurements must be sampled internally to the storage product  
448 at a rate of greater than or equal to 1 measurement per contiguous 10 second period.

449 ii. *Inlet air temperature*: Inlet air temperature measurements must be sampled internally to the  
450 storage product at a rate of greater than or equal to 1 measurement every 10 seconds.

451 iii. *Timestamping*: Systems that implement time stamping of environmental data shall sample  
452 internally to the storage product data at a rate of greater than or equal to 1 measurement  
453 every 30 seconds.

454 iv. *Management Software*: All sampled measurements shall be made available to external  
455 management software either via an on-demand pull method, or via a coordinated push  
456 method. In either case the system's management software is responsible for establishing  
457 the data delivery time scale while the storage product is responsible to assuring data  
458 delivered meets the above sampling and currency requirements.

459 3.6.4 Documentation Requirements: The following information shall be included in the data submission:

460 i. Guaranteed accuracy levels for power and temperature measurements, and

461 ii. The time period used for data averaging (if present).

## 462 4 TESTING

463 **4.1 Test Methods**

464 4.1.1 Test methods identified in Table 12 shall be used for purposes of evaluating active and idle  
465 state storage product energy efficiency.

466 **Table 12: Test Methods for ENERGY STAR Certification**

Product Type	Test Method
All	ENERGY STAR Test Method for Data Center Storage Equipment, Rev. April 2020.

467 **Note:** The test method reference has been updated to reflect the date for the current draft test method.

468 **4.2 Number of Units Required for Testing**

469 4.2.1 Representative Models shall be selected for testing per the following requirements:

- 470 i. For certification of an individual product model, a product configuration equivalent to that  
471 which is intended to be marketed and labeled as ENERGY STAR is considered the  
472 Representative Model;
- 473 ii. For certification of a product family one or more Optimization Configurations shall be tested  
474 and submitted. Within the family covered by one or more Optimal Configurations,  
475 manufacturers continue to be held accountable for any efficiency claims made about their  
476 products, including those not tested or for which data was not reported;

477 **5 EFFECTIVE DATE**

478 5.1.1 Effective Date: The Version 2.0 ENERGY STAR Data Center Storage specification shall take  
479 effect on **March 15, 2021**. To certify for ENERGY STAR, a product model shall meet the  
480 ENERGY STAR specification in effect on its date of manufacture. The date of manufacture is  
481 specific to each unit and is the date on which a unit is considered to be completely assembled.

482 **Note:** EPA anticipates completing the Version 8.0 process no later than June 15, 2020 with an effective  
483 date of March 15, 2021.

484 5.1.2 Future Specification Revisions: EPA reserves the right to change this specification should  
485 technological and/or market changes affect its usefulness to consumers, industry, or the  
486 environment. In keeping with current policy, revisions to the specification are arrived at through  
487 stakeholder discussions. In the event of a specification revision, please note that the ENERGY  
488 STAR certification is not automatically granted for the life of a product model.

489 **6 CONSIDERATIONS FOR FUTURE REVISIONS**

490  
491 6.1 **Active State Efficiency Criteria for File I/O Products:** EPA intends to set active state efficiency  
492 criteria in Version 3.0 for all File I/O storage products in which it has enough data to adequately  
493 differentiate products.