



ENERGY STAR® Program Requirements Product Specification for Large Network Equipment

Final Draft Test Method Rev. June-2015

1 OVERVIEW

The following test method shall be used for determining product compliance with requirements in the ENERGY STAR Eligibility Criteria for Large Network Equipment (LNE).

2 APPLICABILITY

The following test method is applicable to all eligible products covered by the scope as defined in Section 2 of the ENERGY STAR Draft 2 Eligibility Criteria for Large Network Equipment, but test requirements are dependent upon the feature set of the product under evaluation. The following guidelines shall be used to determine the applicability of each section of this document:

- One or both procedures in Section 6 shall be conducted on eligible products that are not High Port Count products.
- The procedures in Section 7 shall be conducted on eligible products that are High Port Count products.

Note: The Applicability section has been updated to indicate that High Port Count products are required to perform only the specialized testing in Section 7, while all other products are required to perform only the testing in Section 6.

3 DEFINITIONS

Unless otherwise specified, all terms used in this document are consistent with the definitions in the ENERGY STAR Large Network Equipment Specification.

A) Abbreviations and Units:

- 1) ac: Alternating current
- 2) ATIS: Alliance for Telecommunications Industry Solutions
- 3) bps: Bits per second
- 4) C: Celsius
- 5) dc: Direct current
- 6) FCS: Frame check sequence
- 7) GBIC: Gigabit interface converter
- 8) Hz: Hertz
- 9) IEEE: Institute of Electrical and Electronics Engineers
- 10) IMIX: Internet mix
- 11) IP: Internet protocol
- 12) LNE: Large network equipment

- 32 13) MAC: Medium access control
- 33 14) MUT: Module under test
- 34 15) NDR: Non-drop rate
- 35 16) OSI: Open systems interconnection
- 36 17) PDU: Power distribution unit
- 37 18) PSU: Power supply unit
- 38 19) RMS: Root mean square
- 39 20) SFD: Start of frame delimiter
- 40 21) SFP: Small form-factor pluggable
- 41 22) UPS: Uninterruptible power supply
- 42 23) UUT: Unit under test
- 43 24) V: Volts
- 44 25) VLU: Very low utilization
- 45 26) W: Watt

46 B) Definitions:

- 47 1) High Port Count Product: An LNE product that has more than 200 data ports, each of which has a
- 48 maximum rated data throughput rate of at least 10 Gbps.

49 **Note:** DOE recognizes that there can be a large cost burden associated with testing products with many
50 data ports that have a rated throughput of at least 10Gbps. For this reason, the Final Draft Test Method
51 classifies products with more than 200 data ports that each have a throughput of at least 10Gbps as High
52 Port Count products. Such products are required to perform specialized testing that includes a snaked
53 data traffic configuration in order to reduce test burden. DOE requests stakeholder feedback regarding
54 this proposed definition. Specifically, is 200 10Gbps ports an appropriate threshold to High Port Count
55 products?

- 56 2) Internet Mix (IMIX) Traffic: A stateless traffic profile that contains a mixture of frame sizes
- 57 statistically similar to a composition observed in the Internet¹.
- 58 3) Maximum Non-Drop Rate (NDR): The highest observed system throughput, measured in bits per
- 59 second (bps), at which all data packets received by the unit under test (UUT) are processed and
- 60 correctly transmitted.
- 61 4) System Throughput: The sum of the data link bits processed by the UUT per second in the
- 62 egress direction, including frame preamble, Start Frame Delimiter (SFD), Frame Check Sequence
- 63 (FCS), and minimum interpacket gap.
- 64 5) System Utilization: The system throughput expressed as a percentage of the system's measured
- 65 NDR.
- 66 6) Traffic Profile: The statistical distribution of the size/type of the data sent through the UUT.

¹ For further information regarding IMIX, refer to Spirent Communications – Test Methodology Journal: IMIX (Internet Mix) Journal, March 2006.

67 **4 TEST SETUP**

68 A) Input Power: Input power for alternating current (ac) LNE shall be as specified in Table 1 and Table 2.
 69 Input power for direct current (dc) LNE shall be as specified in Table 3. The input power frequency for
 70 ac LNE shall be as specified in Table 4.

71
 72 **Table 1: Input Power Requirements for Ac-powered Products with Nameplate Rated Power Less**
 73 **Than 1500 Watts (W)**

Product Type	Supply Voltage	Voltage Tolerance	Maximum Total Harmonic Distortion
Ac single-phase powered LNE	115 V ac 230 V ac	+/- 1.0%	2.0%, up to and including the 13th harmonic
Ac three-phase powered LNE	208 V ac 400 Vac		

74

75 **Table 2: Input Power Requirements for Ac-powered Products with Nameplate Rated Power Greater**
 76 **Than or Equal to 1500 W**

Product Type	Supply Voltage	Voltage Tolerance	Maximum Total Harmonic Distortion
Ac single-phase powered LNE	115 V ac 230 V ac	+/- 4.0%	5.0%, up to and including the 13th harmonic
Ac three-phase powered LNE	208 V ac 400 Vac		

77

78 **Table 3: Input Power Requirements for Dc-powered Products**

Product Type	Supply Voltage	Voltage Tolerance
Dc powered LNE rated for -48 V dc	-53 V dc	+/- 2.0 V

79

Table 4: Input Power Frequency Requirements for Ac-powered Products

Supply Voltage	Frequency	Frequency Tolerance
115 V ac	60 Hertz (Hz)	+/-1.0%
230 V ac	50 Hz or 60 Hz	
208 V ac, Three-phase	60 Hz	
400 V ac, Three-phase	50 Hz or 60 Hz	

81

82 B) Ambient Temperature: The ambient temperature in front of the main airflow inlet of the UUT during all
83 power measurement tests shall be greater than 27.0°C and less than 30.0°C.

84 **Note:** The Draft 2 Test Method requires an ambient temperature of 27°C +/- 1°C. The range was
85 broadened from the previous draft in order to ensure test repeatability, since there can be a wide variation
86 in the power used by cooling fans depending on the ambient temperature. In response to the publication
87 of the Draft 2 Test Method, DOE received comment that the narrow range of this requirement might
88 introduce unnecessary test burden. Further, stakeholders commented that ATIS 06000015.2013 allows
89 alternative methods to be used that avoid the necessity of a narrow ambient temperature range.

90 Section 5.7 of ATIS 06000015.2013 requires that power usage attributable to the UUT's cooling systems
91 be representative of operation at 27°C, and allows one of three methods to be used. Two of these options
92 are not being considered for inclusion since one requires that the fan speed be fixed, and the other
93 requires that a calculated power offset be applied to the measured power value. DOE is not aware of a
94 verifiable method to determine such a representative fixed fan speed nor power offset to simulate
95 operation at 27°C. One of the allowable methods in Section 5.7 of ATIS 06000015.2013 requires that the
96 UUT be tested at a temperature greater than 27°C. Based on this, Section 4.B) of the Final Draft Test
97 Method requires that the ambient temperature be greater than 27.0°C and less than 30.0°C. DOE
98 requests comment on the proposed requirements.

99 1) Temperature Measurement Location and Accuracy: Temperature must be measured no more
100 than 50 millimeters in front of (upwind of) the main airflow inlet of the UUT and reported by the
101 sensor with an overall accuracy of ± 0.5 °C or better. If the UUT has more than one main airflow
102 inlet, then the temperature must be measured simultaneously from the two main airflow inlets that
103 are separated by the greatest spatial distance. The average of the two measurements must meet
104 the ambient temperature requirement of Section 4.B).

105 **Note:** DOE recognizes that some LNE products may have more than one main airflow inlet. For this
106 reason the Final Draft Test Method includes a method to help ensure that the measured temperature is
107 accurate across a wider spatial geometry.

108 C) Relative Humidity: Relative humidity shall be within 15% and 80%.

109 D) Power Meter: Power meters shall possess the following attributes:

110 1) Reporting and Measurement Units:

111 a) If the UUT is a dc powered LNE, the power meter shall report power, voltage, and current.

- 112 b) If the UUT is an ac powered LNE, the power meter shall report true root mean square (RMS)
113 power, voltage, current, and power factor.
- 114 2) Calibration: The meter shall have been calibrated within a year of the test date, by a standard
115 traceable to National Institute of Standards and Technology [USA] or a counterpart national
116 metrology institute in other countries.
- 117 3) Crest Factor (ac powered LNE only): An available current crest factor of 3 or more at its rated
118 range value. For power meters that do not specify the current crest factor, the power meter must
119 be capable of measuring an amperage spike of at least 3 times the maximum amperage
120 measured during any 1 second sample.
- 121 4) Minimum Bandwidth of Input Circuitry: 80.0 kHz.
- 122 5) Minimum Digitizing Sample Rate: 40.0 kHz.
- 123 6) Minimum Resolution:
- 124 a) 0.01 W for measurement values less than 10 W;
- 125 b) 0.1 W for measurement values from 10 W to 100 W; and
- 126 c) 1.0 W for measurement values greater than 100 W.
- 127 7) Measurement Accuracy: Power measurements shall be reported by the power meter with an
128 overall accuracy of 1% or better for all measured power values.
- 129 E) Network Test Equipment (Test Equipment): The Test Equipment used for Section 6 and Section 7
130 must comply with the following requirements:
- 131 1) Number of Ports: The Test Equipment shall have at least one port for each port required to be
132 connected to a port on the UUT, as stated in Section 5.1.A)5)a). Each connected port on the Test
133 Equipment shall be capable of sending and receiving data to and from the UUT at the highest
134 operable line-rate standard corresponding to the connected port on the UUT.
- 135 2) Traffic Generation: The Test Equipment must be capable of generating traffic that complies with
136 the requirements in Section 5.1.A)5)d).

137 5 TEST CONDUCT

138 5.1 UUT and Test Equipment Configuration

- 139 A) Variable Load Testing: All testing performed in Section 6 and Section 7 shall adhere to the
140 requirements provided in the Alliance for Telecommunications Industry Solutions (ATIS)-
141 0600015.03.2013 standard unless otherwise specified in this document. All testing performed in
142 Section 6 and Section 7 shall be conducted as follows:
- 143 1) As-shipped Condition: Products shall be tested in their “as-shipped” configuration, which includes
144 both hardware configuration and system settings, unless otherwise specified in this test method.
- 145 a) LNE Requiring Initial Configuration: If the UUT cannot be tested in its “as-shipped” condition
146 without additional initial configuration, then the UUT shall be configured according to the
147 instructions provided in the UUT’s user manual. Any supporting materials (e.g., configuration
148 files) that are included with the UUT or publicly available may be used if required for correct
149 UUT functionality.
- 150 b) Mid-test UUT Reconfiguration: The UUT shall be configured prior to running the test
151 procedures in Section 6 or Section 7. No reconfiguration of the UUT shall occur following the
152 commencement of the procedures in Section 6 or Section 7, unless otherwise specified in
153 this test method.

- 154 2) Measurement Location: All power measurements shall be taken at a point between the ac or dc
155 power source and the UUT. No uninterruptible power supply (UPS) units may be connected
156 between the power meter and the UUT.
- 157 3) Air Flow Management: Any airflow directly surrounding the UUT during testing shall only be
158 generated by fans or cooling devices that are standard components of the UUT.
- 159 4) Power Supply Units (PSUs): All installed PSUs included with the UUT must be operational and
160 connected to an appropriate power source, unless otherwise specified in this test method.
- 161 a) UUTs with Multiple PSUs: If the UUT has more than one PSU, then any method may be used
162 to aggregate the power so long as the method used does not introduce a measurement error
163 greater than 1% of the total measured power.

164 **Note:** Based on stakeholder feedback, DOE has added back the ability to use power distribution units
165 (PDUs) for products with multiple PSUs. The Final Draft Test Method now permits any method to be
166 employed in aggregating the power usage of multiple PSUs, so long as that method does not have a
167 substantial power overhead.

- 168 5) I/O and Network Connection: UUT ports shall be connected as indicated in Section 5.2.A)4). All
169 connected ports shall be ready to pass traffic for the entirety of the testing performed in Section 6.
- 170 a) Number of Ports Connected: The number of ports required to be connected to the Test
171 Equipment are as follows:
- 172 i. Full-port Test: Section 6.1 shall be performed with all traffic-capable UUT ports
173 connected to the Test Equipment.
- 174 ii. Half-port Test in Full-mesh Configuration: If the UUT is tested in the Full-mesh
175 configuration according to Section 5.2.A)4), then Section 6.2 shall be performed with half
176 of the traffic-capable UUT ports connected to the Test Equipment. Round up to the
177 nearest integer value if there are an odd number of ports. The ports to be connected shall
178 be chosen at random.
- 179 iii. Half-port Test in Dual-group Partial Mesh Configuration: If the UUT is tested in the Dual-
180 group Partial Mesh configuration according to Section 5.2.A)4), then Section 6.2 shall be
181 performed with half of the UUT downlink ports connected to the Test Equipment. Round
182 up to the nearest integer value if there are an odd number of ports. The ports to be
183 connected shall be chosen at random. All of the UUT uplink ports shall be connected
184 during testing.
- 185 iv. High Port Count Power Measurement Test: Section 7.1 shall be performed with two UUT
186 ports connected to corresponding ports on the test equipment for each distinct stream of
187 snaked data traffic. The ports shall be connected according to Section 5.2.B).
- 188 v. High Port Count Throughput Measurement Test: Section 7.27.2 shall be performed with
189 all ports on the modules under test (MUTs) connected to corresponding ports on the Test
190 Equipment, and there shall be two UUT ports connected to corresponding ports on the
191 test equipment for each distinct stream of snaked data traffic. The ports shall be
192 connected according to Section 5.2.C).

193
194
195
196

197
198
199
200

201
202
203
204

205
206

207
208
209

210
211
212

213
214
215
216
217

218

Note: The Final Draft Test Method includes port configuration requirements that support added testing for High Port Count products found in Section 7. DOE believes these requirements to be representative of those already used by manufacturers to implement snaked traffic testing. DOE requests stakeholder comment on how accurately the requirements align with how snaked traffic is actually implemented.

- b) System Management Ports: Any port on the UUT that does not pass traffic, and is solely intended for device management may be connected as instructed by the manufacturer during testing. If no manufacturer instruction is provided, system management ports shall be disconnected during testing.
- c) Energy Efficient Ethernet (EEE): If the UUT has ports that provide EEE², the UUT shall be connected to network ports that also support EEE. This can be done either by having the traffic source provide the EEE ports, or placing an intermediate network device between the traffic source and UUT.
- d) Traffic Generation: The traffic generated by the Test Equipment for Section 6 and Section 7 must comply with the following requirements:
 - i. Packet Format: The traffic shall be formatted as Internet Protocol (IP) version 4 (IPv4³) with randomized IPv4 data field values. The IPv4 packets shall be transported using Ethernet⁴.
 - ii. Generated Packet Size Statistical Distribution: The traffic shall consist of packet sizes whose generation frequency is statistically described by the Simple IMIX distribution, defined in Table 5.
 - iii. Idle-link Period Distribution: All traffic shall be generated so that the same interpacket gap separates each transmitted Ethernet packet. In other words, there should be a fixed spacing in time between Ethernet frames. However, frames shall not be sent to all ports simultaneously (i.e. the fixed spacing in time should not occur simultaneously on all ports).

Table 5: Simple IMIX Packet Distribution⁵

IP Packet Size (Bytes)	Ethernet Frame Size ⁶ (Bytes)	Proportion of Total Generated IP Packets	Proportion of Total Generated Ethernet Packet Throughput ⁷
40	64	7 parts (~58.33%)	~12.83%
576	594	4 parts (~33.33%)	~53.60%
1500	1518	1 part (~8.33%)	~33.57%

² As defined in Clause 78 of IEEE 802.3 (originally specified in IEEE 802.3az).

³ "Internet Protocol". Sep 1981. RFC 791.

⁴ As defined in IEEE 802.3.

⁵ "Table D.1: Simple IMIX", Annex D: IMIX Traffic, ATIS – 0600015.03.2013

⁶ Ethernet frame sizes do not include preamble, start of frame delimiter (SFD), or minimum interpacket gap.

⁷ Throughput is based on the listed Ethernet frame size plus 7-byte preamble, 1-byte SFD, and 12-byte minimum interpacket gap per transmitted packet.




Figure 1: Relationship of Different Components of Test Data⁸

Note: The Draft 2 Test Method included "Physical Interface Requirements" that limited what type of interfaces, ports, and pluggable modules could be used on the UUT during testing. DOE has not included these requirements in the Final Draft Test Method, since they will be addressed in future drafts and/or versions of the Specification.

e) Cabling Requirements: Each copper-based cable used during testing shall be no longer than 5 meters in length.

f) Interchangeable Modules Installed in High Port Count Products: If the UUT is a High Port Count product, then for each distinct type of interchangeable module installed in the UUT that can change the port configuration, there must be a total of at least two (2) identical such modules installed. For example, there cannot be just one of a certain type of line card installed; there must be at least two of each type installed.

Note: The Final Draft Test Method requires High Port Count products to have at least two of each interchangeable module (e.g., line card) installed. In Section 7.2, the maximum throughput is measured using two identical modules in order to ensure that test data traffic is not simply processed locally on the module, but rather, forced to be handled at a system level. DOE believes this requirement to be consistent with how High Port Count products are currently tested, and does not believe the restriction in product configuration to impose unnecessary burden.

5.2 UUT and Test Equipment Preparation

A) Variable Load Test Preparation: Prior to performing testing outlined in Section 6 or Section 7, prepare the UUT according to the following steps:

1) Record the UUT manufacturer, model name, and configuration details including, but not limited to, number of ports, port throughput, additional built in interface ports, and number of fans.

2) If the UUT is a rack device, install it in a test rack. If the UUT is not a rack device, place it in a stable location where it will not be disturbed. Once set up, the UUT shall not be physically moved until testing is complete.

⁸ The diagram is included as an example to clarify certain terms, and is not drawn to scale. Certain optional elements not included in the diagram, such as VLAN tagging, may be used when appropriate.

- 247 3) Configure the Test equipment for the correct traffic workload and profile as described in
248 5.1A)a)d).
- 249 4) Connect UUT ports to the Test equipment in the appropriate topology according to the following:
- 250 a) The dual-group partial mesh topology shall be used if there are clear designations between
251 downlink and uplink ports listed on the UUT, or if downlink and uplink ports are indicated in
252 materials, such as instruction manuals, provided by the manufacturer. In this configuration,
253 traffic must always flow from an uplink port to a downlink port or vice versa. If the UUT is a
254 High Port Count product, then it shall be configured according to the requirements in Sections
255 5.2.B) and 5.2.C).
- 256 b) The full mesh topology shall be used if there are no clear designations between downlink and
257 uplink ports listed on the UUT or if downlink and uplink ports are not indicated in materials,
258 such as instruction manuals, provided by the manufacturer. In this configuration, traffic from
259 each data port is permitted to flow to any other data port on the UUT. If the UUT is a High
260 Port Count product, then it shall be configured according to the requirements in Sections
261 5.2.B) and 5.2.C).
- 262 5) Connect the UUT to an appropriate ac or dc voltage source using the following guidelines:
- 263 a) No devices shall be connected between the power meter(s) and the UUT, except for PDUs
264 as described in section 5.1.A)5)a), if applicable;
- 265 b) The power meter shall remain connected until all testing is complete;
- 266 c) Power values shall be recorded from the power meter in compliance with Section 4.D).
- 267 6) If applicable, prepare the UUT according to the requirements provided in Section 5.1.A)1)a).
- 268 7) If the input voltage is ac, then record the input RMS voltage and input frequency. If the input
269 voltage is dc, then record the reported input voltage.
- 270 B) High Port Count Power Measurement Test Preparation: Prior to performing testing outlined in Section
271 7.1, prepare the UUT according to the following steps:
- 272 1) Connect all data ports in a snaked data traffic configuration, using the following guidelines:
- 273 a) For each group of data ports that have the same maximum rated throughput rate, there shall
274 be a single snaked data traffic stream. For example, if the UUT has 10GbE ports and 1GbE
275 ports, then two separate snaked data traffic streams shall be used.
- 276 b) Each snaked data traffic stream shall initiate at a test equipment data port, flowing to and
277 then between UUT data ports using a combination of external physical connections (e.g.,
278 cabling) and internal virtual connections (e.g., VLAN), terminating at a test equipment data
279 port. The traffic stream shall only flow between ports of the same maximum rated data
280 throughput rate.
- 281 c) As much as is possible for the modular system's configuration, all internal virtual connections
282 must be made between data ports on different interchangeable modules. If the data port
283 count or configuration makes this impossible, an appropriate alternate configuration may be
284 used, but must be documented.

285 **Note:** The Final Draft Test Method includes configuration requirements for the High Port Count Power
286 Measurement Test. The main difference from normal testing is that this configuration relies on snaked
287 data traffic in order to reduce the number of ports needed on the test equipment. DOE has received
288 feedback from stakeholders indicating that the power usage of a High Port Count product operating with a
289 snaked data traffic configuration is approximately the same as that of the product operating in a full mesh
290 configuration. It is for this reason that the snaked data traffic configuration is used in the High Port Count
291 Power Measurement Test. Further, DOE has included a requirement that all internal virtual connections
292 must be made between different interchangeable modules, if possible. This is to prevent a High Port
293 Count product from handling data traffic locally on a single interchangeable module. DOE requests
294 stakeholder feedback on the proposed configuration requirements for the High Port Count Power
295 Measurement Test.

296 C) High Port Count Throughput Measurement Test Preparation: The High Port Count Throughput
297 Measurement Test is performed once for each distinct type of interchangeable module installed that
298 can change the port configuration. Prior to performing each required iteration of testing outlined in
299 Section 7.2, prepare the UUT according to the following steps:

- 300 1) Choose two (2) of the installed interchangeable modules, each of which is identical and of the
301 desired type to be tested in the given test iteration. These chosen interchangeable modules are
302 referred to as the MUTs for the duration of the given test iteration.
- 303 2) Connect each data port on the MUTs to a corresponding data port on the Test Equipment.
304 Traffic from each data port shall be permitted to flow to any other data port on the MUTs. This
305 part of the UUT configuration represents an “isolated full mesh” topology.
- 306 3) Connect all remaining data ports of the UUT (i.e., those not on the MUTs) in a snaked data
307 traffic configuration according to the requirements in Section 5.2.B)1).

308 **Note:** The Final Draft Test Method includes configuration requirements for the High Port Count
309 Throughput Measurement Test. This test measures the maximum NDR for two identical modules in an
310 isolated full-mesh configuration, in order to associate a maximum throughput with those modules. The
311 remaining ports on the system are configured in a snaked data traffic configuration in order to “stress” the
312 UUT, providing a more representative scenario. DOE recognizes that this approach differs from the
313 “modular method” included in the ATIS procedure. However, while the ATIS modular method is used to
314 measure the throughput and power of a single module installed in a system, the High Port Count test in
315 the Final Draft Test Method is intended to provide such measurements of a full system, with modules
316 installed as they would be in its intended deployment. DOE requests stakeholder feedback on the
317 configuration proposed to be used for the High Port Count Throughput Measurement Test.

318 **6 TEST PROCEDURE FOR ALL PRODUCTS EXCEPT HIGH PORT** 319 **COUNT PRODUCTS**

320 **6.1 Full-port Variable Load Energy Efficiency Test**

- 321 A) Power on the UUT, either by switching it on or connecting it to mains power.
- 322 B) Let the UUT stabilize for 15 minutes.
- 323 C) Determine the maximum load (L_{max}) that can be sustained at NDR. Any method may be used to
324 obtain this value, but the method used shall be reported. There is no time limit for this run. The run is
325 complete after L_{max} is determined. Record L_{max} .
- 326 D) The following tests shall be completed in the order specified and shall have no greater than 300
327 seconds idle time between them.

- 328 1) Full Load:
- 329 a) Apply L_{max} , obtained in Section 6.1.C) to the UUT for 15 minutes.
- 330 b) Record power values for the entire 15-minute test period.
- 331 c) Calculate and report the average power value (P_{100}).
- 332 2) Thirty Percent Load:
- 333 a) Calculate and report the Thirty Percent Load throughput (L_{30}), by multiplying L_{max} by 0.30
- 334 ($L_{30} = 0.30 * L_{max}$)
- 335 b) Run the test for 15 minutes, applying a traffic load of L_{30} .
- 336 c) Record power values for the entire 15 minute period.
- 337 d) Calculate and report the average value (P_{30}).
- 338 3) Very Low Utilization (VLU):
- 339 a) Calculate and report the VLU throughput (L_{VLU}), by multiplying L_{max} by 10^{-4} ($L_{VLU} = 10^{-4} *$
- 340 L_{max})
- 341 b) Run the test for 15 minutes, applying a traffic load of L_{VLU} .
- 342 c) Record power values for the entire 15 minute period.
- 343 d) Calculate and report the average value (P_{VLU}).
- 344 E) If packet loss occurs during any of the tests specified in Section 6.1.D), the UUT must be retested
- 345 beginning with Section 6.1.C).

346 6.2 Half-port Variable Load Energy Efficiency Test

- 347 A) Power on the UUT, either by switching it on or connecting it to mains power.
- 348 B) Let the UUT stabilize for 15 minutes.
- 349 C) Determine the maximum load (L_{max}) that can be sustained at NDR. Any method may be used to
- 350 obtain this value, but the method used shall be reported. There is no time limit for this run. The run is
- 351 complete after L_{max} is determined. Record L_{max} .
- 352 D) The following tests shall be completed in the order specified and shall have no greater than 300
- 353 seconds idle time between them.
- 354 1) Full Load:
- 355 a) Apply L_{max} , obtained in Section 6.2.C) to the UUT for 15 minutes.
- 356 b) Record power values for the entire 15 minute test period.
- 357 c) Calculate and report the average power value (P_{100}).
- 358 2) Ten Percent Load:
- 359 a) Calculate and report the Ten Percent Load throughput (L_{10}), by multiplying L_{max} by 0.10
- 360 ($L_{10} = 0.10 * L_{max}$)
- 361 b) Run the test for 15 minutes, applying a traffic load of L_{10} .
- 362 c) Record power values for the entire 15 minute period.
- 363 d) Calculate and report the average value (P_{10}).
- 364 3) Very Low Utilization (VLU):
- 365 a) Calculate and report the VLU throughput (L_{VLU}), by multiplying L_{max} by 10^{-4} ($L_{VLU} = 10^{-4} *$
- 366 L_{max})
- 367 b) Run the test for 15 minutes, applying a traffic load of L_{VLU} .

- 368 c) Record power values for the entire 15 minute period.
369 d) Calculate and report the average value (P_{VLU}).
370 E) If packet loss occurs during any of the tests specified in Section 6.2.D), the UUT must be retested
371 beginning with Section 6.2.C)

372 7 TEST PROCEDURE FOR HIGH PORT COUNT PRODUCTS

373 If the UUT is a High Port Count product, then the procedures in this section shall be performed as follows:

- 374 A) Perform the High Port Count Power Measurement Test in Section 7.1 once; and
375 B) Perform the High Port Count Throughput Measurement Test in Section 7.2 once for each distinct type
376 of interchangeable module installed that can change the port configuration.

377 7.1 High Port Count Power Measurement Test

- 378 A) Power on the UUT, either by switching it on or connecting it to mains power.
379 B) Let the UUT stabilize for 15 minutes.
380 C) Determine the maximum load (L_{max}) that can be sustained simultaneously at NDR for the MUTs and
381 each snaked data traffic stream. Any method may be used to obtain these values, but the method
382 used shall be reported. There is no time limit for this run. The run is complete after L_{max} is determined
383 for the MUTs and each snaked data traffic stream. Record each of these L_{max} values.
384 D) The following tests shall be completed in the order specified and shall have no greater than 300
385 seconds idle time between them.
386 1) Full Load:
387 a) Apply L_{max} values, obtained in Section 7.1.C), to the MUTs and to each snaked data traffic
388 stream, respectively, for 15 minutes.
389 b) Record the total UUT power usage for the entire 15-minute test period.
390 c) Record the average power value (P_{100}).
391 2) Thirty Percent Load:
392 a) Calculate and report the Thirty Percent Load throughputs (L_{30}), by multiplying L_{max} values by
393 0.30 ($L_{30} = 0.30 * L_{max}$)
394 b) Run the test for 15 minutes, applying a traffic load of L_{30} .
395 c) Record the total UUT power usage for the entire 15-minute test period.
396 d) Calculate and report the average value (P_{30}).
397 3) Very Low Utilization (VLU):
398 a) Calculate and report the VLU throughputs (L_{VLU}), by multiplying L_{max} values by 10^{-4} ($L_{VLU} =$
399 $10^{-4} * L_{max}$)
400 b) Run the test for 15 minutes, applying a traffic load of L_{VLU} .
401 c) Record total UUT power usage for the entire 15-minute period.
402 d) Calculate and report the average value (P_{VLU}).
403 E) If packet loss occurs during any of the tests specified in Section 7.1.D), the UUT must be retested
404 beginning with Section 7.1.C).

405 7.2 High Port Count Throughput Measurement Test

- 406 A) Power on the UUT, either by switching it on or connecting it to mains power.

- 407 B) Let the UUT stabilize for 15 minutes.
- 408 C) Determine the maximum load (L_{max}) that can be sustained at NDR for the MUTs and each snaked
 409 data traffic stream. Any method may be used to obtain these values, but the method used shall be
 410 reported. There is no time limit for this run. The run is complete after L_{max} is determined for the MUTs
 411 and each snaked data traffic stream. Record the combined L_{max} for the MUTs.
- 412 D) For each distinct type of interchangeable module installed in the UUT, reconfigure the UUT according
 413 to Section 5.2.C) and repeat step 7.2.C) until the maximum load of each distinct type of installed
 414 interchangeable module has been measured.
- 415 E) Calculate and report the aggregate maximum throughput (L_{tot}) using the following equation:
 416

$$L_{tot} = \sum_{k=1}^{N_{tot}} N_k \cdot \frac{L_{max_k}}{2}$$

Where:

L_{tot} is the UUT aggregate maximum throughput

N_{tot} is the total number of distinct types of interchangeable modules installed in the UUT

N_k is the total number of interchangeable modules installed in the UUT of type, “k”

L_{max_k} is the maximum load measured for the interchangeable module of type, “k”, in Section 7.2.

417

418 **8 REFERENCES**

- 419 A) Alliance for Telecommunications Industry Solutions (ATIS) – 0600015.03.2013 Energy Efficiency for
 420 Telecommunication Equipment: Methodology for Measurement and Reporting for Router and
 421 Ethernet Switch Products
- 422 B) Spirent Communications – Test Methodology Journal: IMIX (Internet Mix) Journal, March 2006.
- 423 C) IEEE 802.3-2012: IEEE Standard for Ethernet.