



# ENERGY STAR® Program Requirements Product Specification for Computers

## Eligibility Criteria Draft 1, Version 9.0

1 Following is the **Draft 1, Version 9** ENERGY STAR Product Specification for Computers. A product shall  
2 meet all of the identified criteria if it is to earn the ENERGY STAR.

### 3 **1 DEFINITIONS**

#### 4 A) Product Types:

- 5 1) Computer: A device which performs logical operations and processes data. For the purposes of  
6 this specification, computers include both stationary and portable units, including Desktop  
7 Computers, Integrated Desktop Computers, Notebook Computers, Small-Scale Servers, Thin  
8 Clients, and Workstations. Although computers are capable of using input devices and displays,  
9 such devices are not required to be included with the computer upon shipment. Computers are  
10 composed of, at a minimum:
- 11 a) A central processing unit (CPU) to perform operations. If no CPU is present, then the device  
12 must function as a client gateway to a server which acts as a computational CPU;
  - 13 b) User input devices such as a keyboard, mouse, or touchpad; and
  - 14 c) An Integrated Display screen and/or the ability to support an external display screen to output  
15 information.
- 16 2) Desktop Computer: A computer whose main unit is designed to be located in a permanent  
17 location, often on a desk or on the floor. Desktop computers are not designed for portability and  
18 are designed for use with an external display, keyboard, and mouse. Desktop computers are  
19 intended for a broad range of home and office applications, including point of sale applications.
- 20 a) Integrated Desktop Computer: A Desktop Computer in which the computing hardware and  
21 display are integrated into a single housing, and which is connected to ac mains power  
22 through a single cable. Integrated Desktop Computers come in one of two possible forms: (1)  
23 a system where the display and computer are physically combined into a single unit; or (2) a  
24 system packaged as a single system where the display is separate but is connected to the  
25 main chassis by a dc power cord and both the computer and display are powered from a  
26 single power supply. As a subset of Desktop Computers, Integrated Desktop Computers are  
27 typically designed to provide similar functionality as Desktop systems.
- 28 3) Notebook Computer: A computer designed specifically for portability and to be operated for  
29 extended periods of time both with and without a direct connection to an ac mains power source.  
30 Notebook Computers include an Integrated Display, a non-detachable, mechanical keyboard  
31 (using physical, moveable keys), and pointing device.
- 32 a) Mobile Thin Client: A computer meeting the definition of a Thin Client, designed specifically  
33 for portability, and meeting the definition of a Notebook Computer. These products are  
34 considered to be Notebook Computers for the purposes of this specification.
  - 35 b) Two-In-One Notebook: A computer which resembles a traditional Notebook Computer with a  
36 clam shell form factor but has a detachable display which can act as an independent  
37 Slate/Tablet when disconnected. The keyboard and display portions of the product must be  
38 shipped as an integrated unit. Two-In-One Notebooks are considered Notebooks in the  
39 remainder of this specification and are therefore not referenced explicitly.

40 c) Mobile Workstation: A computer which meets the definition of Notebook Computer and is  
41 designed for use in professional workflows such as architecture, engineering, computer aided  
42 drafting, product development, financial applications, scientific applications, and/or content  
43 creation. It must also meet all of the following criteria:

- 44 (1) Has a mean time between failures (MTBF) of at least 13,000 hours;
- 45 (2) Certification by 4 or more Independent Software Vendor (ISV) product certifications in  
46 professional workflows (see examples above). These certifications can be in process,  
47 but partner shall ensure they are completed within 6 months of the date the product  
48 becomes available on the market;
- 49 (3) Supports at least 32 gigabytes of system memory; and
- 50 (4) Supports either:
  - 51 (a) At least one integrated or discrete GPU with frame buffer bandwidth of 96  
52 gigabytes per second or greater; or
  - 53 (b) A total of 4 gigabytes or more of system memory with a bandwidth of 134  
54 gigabytes per second or greater and an integrated GPU.

55 **Note:** EPA received stakeholder feedback recommending updates to the mobile workstation definition to  
56 more closely align with specific workflow types that these products are designed for. EPA has adopted  
57 these changes above.

58 d) Multi-Screen Notebook: A computer which resembles a traditional Notebook Computer with a  
59 clam shell form factor but has a secondary display with touch and/or pen capability that can  
60 be used as a touch screen keyboard in place of a traditional mechanical keyboard. These  
61 products are considered to be Notebook Computers for purposes of this specification.

- 62 4) Slate/Tablet: A computing device designed for portability that meets all of the following criteria:
- 63 a) Includes an integrated display with a diagonal size greater than 7.0 inches and less than 17.4  
64 inches;
  - 65 b) Lacking an integrated, physical attached keyboard in its as-shipped configuration;
  - 66 c) Includes and primarily relies on touchscreen input; (with optional keyboard);
  - 67 d) Includes and primarily relies on a wireless network connection (e.g., Wi-Fi, 3G, etc.); and
  - 68 e) Includes and is primarily powered by an internal battery (with connection to the mains for  
69 battery charging, not primary powering of the device).

70 **Note:** EPA received stakeholder feedback requesting that EPA align the existing slate/tablet definition  
71 with the new definition being used in the EU regulatory space. EPA is proposing to align on the revised  
72 minimum screen size of 7.0" vs. the previous 6.5" referenced in ENERGY STAR Version 8 but is not  
73 adopting the EU language on mobile OS use as EPA has ENERGY STAR certified products slate/tablets  
74 that use operating systems that are not intended for use on smartphones (e.g., standard x86 version of  
75 Windows 10/11). EPA seeks stakeholder feedback on the direction of the market specific to mobile OS  
76 use.

- 77 5) Portable All-In-One Computer: A computing device designed for portability that meets all of the  
78 following criteria:
- 79 a) Includes an integrated display with a diagonal size greater than or equal to 17.4 inches;
  - 80 b) Lacking keyboard integrated into the physical housing of the product in its as-shipped  
81 configuration;
  - 82 c) Includes and primarily relies on touchscreen input; (with optional keyboard);
  - 83 d) Includes wireless network connection (e.g. Wi-Fi, 3G, etc.); and
  - 84 e) Includes an internal battery

- 85 6) E-Reader: A device designed for display and consumption of static images. The display is  
86 characterized by a low refresh rate and a display made of bistable materials where no energy is  
87 needed to maintain a visible image, only to alter the image.
- 88 7) Small-scale Server: A computer that typically uses desktop components in a desktop form factor  
89 but is designed primarily to be a storage host for other computers. Small-scale Servers are  
90 designed to perform functions such as providing network infrastructure services (e.g., archiving)  
91 and hosting data/media. These products are not designed to process information for other  
92 systems or run web servers as a primary function. A Small-scale Server has the following  
93 characteristics:
- 94 a) Designed in a pedestal, tower, or other form factor similar to those of desktop computers  
95 such that all data processing, storage, and network interfacing is contained within one  
96 box/product;
- 97 b) Designed to operate 24 hours/day, 7 days/week, with minimal unscheduled downtime (on the  
98 order of hours/year);
- 99 c) Capable of operating in a simultaneous multi-user environment serving several users through  
100 networked client units; and
- 101 d) Designed for an industry accepted operating system for home or low-end server applications  
102 (e.g., Windows Home Server, Mac OS X Server, Linux, UNIX, Solaris).
- 103 8) Thin Client: An independently-powered computer that relies on a connection to remote computing  
104 resources (e.g., computer server, remote workstation) to obtain primary functionality. Main  
105 computing functions (e.g., program execution, data storage, interaction with other Internet  
106 resources) are provided by the remote computing resources. Thin Clients covered by this  
107 specification are (1) limited to devices with no rotational storage media integral to the computer  
108 and (2) designed for use in a permanent location (e.g. on a desk) and not for portability.
- 109 a) Integrated Thin Client: A Thin Client in which computing hardware and display are  
110 connected to ac mains power through a single cable. Integrated Thin Client computers  
111 come in one of two possible forms: (1) a system where the display and computer are  
112 physically combined into a single unit; or (2) a system packaged as a single system  
113 where the display is separate but is connected to the main chassis by a dc power cord  
114 and both the computer and display are powered from a single power supply. As a subset  
115 of Thin Clients, Integrated Thin Clients are typically designed to provide similar  
116 functionality as Thin Client systems.
- 117 b) Ultra-thin Client: A computer with lesser local resources than a standard Thin Client that  
118 sends raw mouse and keyboard input to a remote computing resource and receives back  
119 raw video from the remote computing resource. Ultra-thin clients cannot interface with  
120 multiple devices simultaneously nor run windowed remote applications due to the lack of  
121 a user-discernible client operating system on the device (i.e., beneath firmware, user  
122 inaccessible).
- 123 9) Workstation: A high-performance, computer used for professional workflows such as architecture,  
124 engineering, computer aided drafting, product development, financial applications, scientific  
125 applications and/or content creation. Workstations covered by this specification (a) are marketed  
126 as a workstation; (b) do not support altering frequency or voltage beyond the CPU and GPU  
127 manufacturers' as shipped operating specifications; and (c) have system hardware that supports  
128 an error-correcting mechanism that detects and corrects data errors with dedicated circuitry on  
129 and across the CPU, interconnect, and system memory. In addition, a workstation must have 4 or  
130 more Independent Software Vendor (ISV) product certifications in professional workflows (see  
131 examples above). These certifications can be in process, but partner shall ensure they are  
132 completed within 6 months of the date the product becomes available on the market.

133  
134  
135  
136  
137

**Note:** Similar to the mobile workstation above, EPA received stakeholder feedback recommending updates to the workstation definition to more closely align with specific workflow types that these products are designed for. The changes EPA is proposing to the workstation definition largely align with the changes to the mobile workstation definition, while also removing some sub-requirements from Version 8 that are no longer relevant in regular workstations.

138  
139  
140  
141

10) Rack-mounted Workstation: A workstation that is designed to be natively rack mounted as described in IEC 60297-3-101:2004. The rack-mounted workstation may be accessed locally by direct connection to the workstation and display or accessed remotely across a network by one or more users.

142  
143  
144

B) Product Category: A second-order classification or sub-type within a product type that is based on product features and installed components. Product categories are used in this specification to determine certification and test requirements.

145

C) Computer Components:

146  
147  
148  
149

1) Central Processing Unit (CPU): A central processing unit, also called a central processor, main processor or just processor, is the electronic circuitry that executes, including but not limited to, floating point or integer-based instructions comprising a computer program. Many processors contain multiple cores to perform these instructions.

150  
151

2) Core: A single functional unit of a CPU that handles software instructions such as arithmetic, floating point, and other data manipulation

152  
153  
154

3) System on Chip (SoC): An integrated circuit that integrates most or all components (CPU, memory, IO, graphics, storage) of a full computer system or other electronic system on a single silicon substrate or package.

155  
156  
157  
158

**Note:** In the discussion guide, EPA requested feedback for any additional definitions that may help better describe products covered by this specification. Stakeholders provided suggested language for CPUs, cores, and SoC's, which EPA is proposing to adopt above. EPA welcomes additional stakeholder feedback on whether any modifications are warranted to finalize these new definitions.

159  
160  
161  
162

4) Graphics Processing Unit (GPU): An integrated circuit, separate from the CPU, designed to accelerate the rendering of either 2D and/or 3D content to displays. A GPU may be mated with a CPU, on the system board of the computer or elsewhere to offload display capabilities from the CPU.

163  
164

5) Discrete Graphics (dGfx): A graphics processor (GPU) which must contain a local memory controller interface and local graphics-specific memory.

165

6) Integrated Graphics (iGfx): A graphics solution that does not contain Discrete Graphics.

166  
167  
168  
169  
170

7) Display: A commercially-available product with a display screen and associated electronics, often encased in a single housing, that as its primary function displays visual information from (1) a computer, workstation or server via one or more inputs (e.g., VGA, DVI, HDMI, DisplayPort, IEEE 1394, USB), (2) external storage (e.g., USB flash drive, memory card), or (3) a network connection.

171  
172

a) Enhanced-performance Integrated Display: An integrated Computer Display that has all of the following features and functionalities:

173  
174

(1) A contrast ratio of at least 60:1 at a horizontal viewing angle of at least 85°, with or without a screen cover glass;

175

(2) A native resolution greater than or equal to 2.3 megapixels (MP); and

176  
177

(3) A color gamut of at least sRGB as defined by IEC 61966-2-1. Shifts in color space are allowable as long as 99% or more of defined sRGB colors are supported.

178 8) External Power Supply (EPS): Also referred to as External Power Adapter. An external power  
179 supply circuit that is used to convert household electric current into dc current or lower-voltage ac  
180 current to operate a consumer product.

181 9) Internal Power Supply (IPS): A component internal to the computer casing and designed to  
182 convert ac voltage from the mains to dc voltage(s) for the purpose of powering the computer  
183 components. For the purposes of this specification, an internal power supply shall be contained  
184 within the computer casing but be separate from the main computer board. The power supply  
185 shall connect to the mains through a single cable with no intermediate circuitry between the  
186 power supply and the mains power. In addition, all power connections from the power supply to  
187 the computer components, with the exception of a DC connection to a display in an Integrated  
188 Desktop Computer, shall be internal to the computer casing (i.e., no external cables running from  
189 the power supply to the computer or individual components). Internal dc-to-dc converters used to  
190 convert a single dc voltage from an external power supply into multiple voltages for use by the  
191 computer are not considered internal power supplies.

192 10) System Memory Bandwidth: The rate at which data can be read or stored into computer system's  
193 memory, expressed in gigabytes per second (GB/s).

194 D) Operational Modes:

195 1) Active State: The power state in which the computer is carrying out useful work in response to a)  
196 prior or concurrent user input or b) prior or concurrent instruction over the network. Active State  
197 includes active processing, seeking data from storage, memory, or cache, including Idle State  
198 time while awaiting further user input and before entering low power modes.

199 2) Idle State: The power state in which the operating system and other software have completed  
200 loading, a user profile has been created, activity is limited to those basic applications that the  
201 system starts by default, and the computer is not in Sleep Mode. Idle State is composed of two  
202 sub-states: Short Idle and Long Idle.

203 a) Long Idle: The mode where the Computer has reached an Idle condition (i.e., 15 minutes  
204 after OS boot or after completing an active workload or after resuming from Sleep Mode)  
205 and the main Computer Display has entered a low-power state where screen contents  
206 cannot be observed (i.e., backlight has been turned off) but remains in the working mode  
207 (ACPI G0/S0). If power management features are enabled as-shipped in the scenario  
208 described in this definition, such features shall engage prior to evaluation of Long Idle  
209 (e.g., display is in a low power state, HDD may have spun-down), but the Computer is  
210 prevented from entering Sleep Mode.  $P_{LONG\_IDLE}$  represents the average power measured  
211 when in the Long Idle Mode.

212 b) Short Idle: The mode where the Computer has reached an Idle condition (i.e., 5 minutes  
213 after OS boot or after completing an active workload or after resuming from Sleep Mode),  
214 the screen is on, and Long Idle power management features have not engaged (e.g.  
215 HDD is spinning and the Computer is prevented from entering sleep mode).  $P_{SHORT\_IDLE}$   
216 represents the average power measured when in the Short Idle Mode.

217 3) Off Mode: The lowest power mode which cannot be switched off (influenced) by the user and that  
218 may persist for an indefinite time when the appliance is connected to the main electricity supply  
219 and used in accordance with the manufacturer's instructions. For systems where ACPI standards  
220 are applicable, Off Mode correlates to ACPI System Level S5 state.

221 4) Sleep Mode: A low power mode that the computer enters automatically after a period of inactivity  
222 or by manual selection. A computer with Sleep capability can quickly "wake" in response to  
223 network connections or user interface devices from initiation of wake event to a readable display.  
224 For systems where ACPI standards are applicable, Sleep Mode most commonly correlates to  
225 ACPI System Level S3 (suspend to RAM) state.  $P_{SLEEP}$  represents the average power measured  
226 when in the Sleep Mode.

227 5) Alternative Low Power Mode (ALPM): A low power mode that the computer enters automatically  
228 after a period of inactivity or by manual selection that is defined by the display turning off and the  
229 computer entering a state of reduced functionality. A computer with Alternative Low Power Mode  
230 must maintain immediate responsiveness to network connections or user interface devices.  $P_{ALPM}$   
231 represents the average power measured when in the Alternative Low Power Mode.

232 E) Networking and Additional Capabilities:

233 1) Additional Internal Storage: Any and all internal hard disk drives (HDD) or solid-state drives (SSD)  
234 installed beyond the primary storage device where the operating system is installed in the  
235 products as shipped state. This definition does not include external drives.

236 2) Energy Efficient Ethernet (EEE): A technology which enables reduced power consumption of  
237 Ethernet interfaces during times of low data throughput. Specified by IEEE 802.3az.

238 3) Full Network Connectivity: The ability of the computer to maintain network presence while in  
239 Sleep Mode or an Alternative Low Power Mode (ALPM) with power demand of less than or equal  
240 to 10 watts and intelligently wake when further processing is required (including occasional  
241 processing required to maintain network presence). Presence of the computer, its network  
242 services and applications, is maintained even though the computer is in an ALPM. From the  
243 vantage point of the network, a computer with full network connectivity that is in ALPM is  
244 functionally equivalent to an idle computer with respect to common applications and usage  
245 models. Full network connectivity in ALPM is not limited to a specific set of protocols but can  
246 cover applications installed after initial installation. Also referred to as “network proxy”  
247 functionality and as described in the *Ecma-393* standard.

248 a) Network Proxy - Base Capability: To maintain addresses and presence on the network while  
249 in Sleep Mode or ALPM, the system handles IPv4 ARP and IPv6 NS/ND.

250 b) Network Proxy - Full Capability: While in Sleep Mode or ALPM, the system supports Base  
251 Capability, Remote Wake, and Service Discovery/Name Services.

252 c) Network Proxy - Remote Wake: While in Sleep Mode or ALPM, the system is capable of  
253 remotely waking upon request from outside the local network. Includes Base Capability.

254 d) Network Proxy - Service Discovery/Name Services: While in Sleep Mode or ALPM, the  
255 system allows for advertising host services and network name. Includes Base Capability.

256 4) Constant Network Connectivity: A capability that allows the wake of system operating system or  
257 software to facilitate communication and downloads from the network (e.g. instant messaging,  
258 email, management and maintenance tasks, etc.)

259 5) Network Interface: The components (hardware and software) whose primary function is to make  
260 the computer capable of communicating over one or more network technologies. Examples of  
261 Network Interfaces are IEEE 802.3 (Ethernet) and IEEE 802.11 (Wi-Fi).

262 6) Wake Event: A user, scheduled, or external event or stimulus that causes the computer to  
263 transition from Sleep Mode or Off Mode to an active state of operation. Examples of wake events  
264 include, but are not limited to: movement of the mouse, keyboard activity, controller input, real-  
265 time clock event, or a button press on the chassis, and in the case of external events, stimulus  
266 conveyed via a remote control, network, modem, etc.

267 7) Wake On LAN (WOL): Functionality which allows a computer to transition from Sleep Mode or Off  
268 Mode to an Active State of operation when directed by a network Wake Event via Ethernet.

269 8) Switchable Graphics: Functionality that allows Discrete Graphics to be disabled when not  
270 required in favor of Integrated Graphics.

271 Note: This functionality allows lower power and lower capability integrated GPUs to render the  
272 display while on battery or when the output graphics are not overly complex while then allowing  
273 the more power consumptive but more capable discrete GPU to provide rendering capability  
274 when required.

- 275 F) Marketing and Shipment Channels:
- 276 1) Enterprise Channels: Sales channels typically used by large and medium-sized business,  
277 government, educational, or other organizations to purchase computers for use in managed  
278 client/server environments.
- 279 2) Model Name: A marketing name that includes reference to the computer model number, product  
280 description, or other branding references.
- 281 3) Model Number: A unique marketing name or identification reference that applies to a specific  
282 hardware and software configuration (e.g., operating system, processor type, memory, GPU), and  
283 is either pre-defined or selected by a customer.
- 284 G) Product Family: A high-level description referring to a group of computers sharing one  
285 chassis/motherboard combination that often contains hundreds of possible hardware and software  
286 configurations. Product models within a family differ from each other according to one or more  
287 characteristics or features that either (1) have no impact on product performance with regard to  
288 ENERGY STAR certification criteria, or (2) are specified herein as acceptable variations within a  
289 product family. For Computers, acceptable variations within a product family include:
- 290 1) Color;
- 291 2) Housing; and
- 292 3) Electronic components other than the chassis/motherboard, such as the processor,  
293 memory, GPU, etc.

## 294 **2 SCOPE**

### 295 **2.1 Included Products**

- 296 2.1.1 Products that meet the definition of a Computer and one of the following Product Type definitions,  
297 as specified herein, are eligible for ENERGY STAR certification, with the exception of products  
298 listed in Section 2.2:
- 299 i. Desktop Computers and Integrated Desktop Computers;
- 300 ii. Notebook Computers;
- 301 iii. Slates/Tablets;
- 302 iv. Portable All-In-One Computers;
- 303 v. Workstations; and
- 304 vi. Thin Clients.

### 305 **2.2 Excluded Products**

- 306 2.2.1 Products that are covered under other ENERGY STAR product specifications are not eligible for  
307 certification under this specification. The list of specifications currently in effect can be found at  
308 [www.energystar.gov/products](http://www.energystar.gov/products).
- 309 2.2.2 The following products are not eligible for certification under this specification:
- 310 i. Docking Stations;
- 311 ii. Game Consoles;
- 312 iii. E-Readers;
- 313 iv. Handheld gaming devices, typically battery powered and intended for use with an integral  
314 display as the primary display;
- 315 v. Mobile Thin Clients not meeting the definition of Notebook Computer;

- 316 vi. Personal Digital Assistant devices (PDAs);
- 317 vii. Point of Sale (POS) products that do not use internal components common to Notebook,
- 318 Desktop, or Integrated Desktop Computers, including a processor, motherboard, and
- 319 memory;
- 320 viii. Slate/Tablet based POS products;
- 321 ix. Handheld Computers and Slates/Tablets which contain cellular voice capability;
- 322 x. Open Pluggable Specification (OPS) modules;
- 323 xi. Ultra-thin Clients; and
- 324 xii. Small-scale Servers.

**Note:** EPA received stakeholder feedback stating that while the specification is not intended to cover OPS modules, it was not fully clear that they were out of scope depending on interpretation of the computer definitions in Section 1 of the specification. To remove any ambiguity, EPA has explicitly added OPS modules as out of scope in this draft.

329

### 330 **3 CERTIFICATION CRITERIA**

#### 331 **3.1 Significant Digits and Rounding**

- 332 3.1.1 All calculations shall be carried out with directly measured (unrounded) values.
- 333 3.1.2 Unless otherwise specified in this specification, compliance with specification limits shall be
- 334 evaluated using directly measured or calculated values without any benefit from rounding.
- 335 3.1.3 Directly measured or calculated values that are submitted for reporting on the ENERGY STAR
- 336 website shall be rounded to the nearest significant digit as expressed in the corresponding
- 337 specification limit.

#### 338 **3.2 General Requirements**

- 339 3.2.1 Power supply test data and test reports from testing entities recognized by EPA to perform power
- 340 supply testing shall be accepted for the purpose of certifying the ENERGY STAR product.
- 341 3.2.2 Internal Power Supply (IPS) Requirements: IPSs used in Computers eligible under this
- 342 specification must meet the following requirements when tested using the *Generalized Internal*
- 343 *Power Supply Efficiency Test Protocol, Rev. 6.7.1* (available at
- 344 [https://www.plugloadsolutions.com/docs/collatrl/print/Generalized\\_Internal\\_Power\\_Supply\\_Efficiency\\_Test\\_Protocol\\_R6.7.1.pdf](https://www.plugloadsolutions.com/docs/collatrl/print/Generalized_Internal_Power_Supply_Efficiency_Test_Protocol_R6.7.1.pdf) ).
- 345
- 346 i. IPS with maximum rated output power less than 75 watts shall meet minimum efficiency
- 347 requirements as specified in Table 1.
- 348 ii. IPS with maximum rated output power greater than or equal to 75 watts shall meet both
- 349 minimum efficiency requirements and minimum power factor requirements, as specified in
- 350 Table 1 and Table 2 as applicable.



351 **Table 1: Requirements for Internal Power Supplies with Rated Output of 500 Watts and Below**

Loading Condition (Percentage of Nameplate Output Current)	Minimum Efficiency	Minimum Power Factor
10%	0.80	
20%	0.85	-
50%	0.88	0.90
100%	0.85	-

352

353 **Table 2: Requirements for Internal Power Supplies with Rated Output Above 500 Watts**

Loading Condition (Percentage of Nameplate Output Current)	Minimum Efficiency	Minimum Power Factor
10%	0.80	
20%	0.87	-
50%	0.90	0.90
100%	0.87	-

354 **Note:** EPA received a detailed analysis of 80Plus data showing that Platinum levels for IPS above 500W  
 355 are likely too aggressive at this time as less than 25% of IPS models are listed at Platinum or above.  
 356 Alternatively, EPA found that Silver levels at or below 500W are warranted as over two thirds of 80Plus  
 357 certified 115V IPS models at or below 500W meet Silver or higher levels.

358 As such, EPA is proposing to maintain existing 80Plus Gold equivalent IPS requirements for products  
 359 with rated output above 500W but raising the requirements to 80Plus Silver equivalent for products with a  
 360 rated output of 500W or lower.

361 EPA also received feedback requesting new IPS requirements at very low loads. However, as discussed  
 362 as part of the Version 8 development, EPA will defer to the 80Plus program to create consensus  
 363 requirements at those low load levels before considering adoption of them. Additionally, it is not clear to  
 364 EPA that the absolute energy savings at those low load levels aren't better addressed by more  
 365 aggressive TEC requirements which the Agency is proposing below.

366 3.2.3 External Power Supply (EPS) Requirements: Single- and Multiple-voltage EPSs shall meet the  
 367 Level VI or higher performance requirements under the International Efficiency Marking Protocol  
 368 when tested according to the Uniform Test Method for Measuring the Energy Consumption of  
 369 External Power Supplies, Appendix Z to 10 CFR Part 430.

- 370 i. Single-voltage EPSs shall include the Level VI or higher marking.
- 371 ii. Adaptive EPSs meeting Level VI or higher shall include the Level VI or higher marking.
- 372 iii. Additional information on the Marking Protocol is available  
 373 at <http://www.regulations.gov/#!documentDetail;D=EERE-2008-BT-STD-0005-0218>

374 3.2.4 Energy Efficient Ethernet (EEE) Requirements: All products which contain one or more Ethernet  
 375 ports with a bandwidth of 1Gb/s or higher shall have EEE enabled as-shipped in each of these  
 376 ports in their as-shipped configuration.

377 **Note:** As noted in the future considerations section of the Version 8 specification after discussions with  
 378 stakeholders as part of that process, EPA now proposes that all ports with a speed of 1Gb/s or higher  
 379 must have EEE enabled as-shipped in order to certify as ENERGY STAR.

380

381 **3.3 Power Management Requirements**

382 3.3.1 Products shall include power management features in their “as-shipped” condition as specified in  
383 Table 3, subject to the following conditions:

384 i. For Thin Clients, the Wake-on-LAN (WOL) requirement shall apply for products designed to  
385 receive software updates from a centrally managed network while in Sleep Mode or in Off  
386 Mode. Thin Clients whose standard software upgrade framework does not require off-hours  
387 scheduling are exempt from the WOL requirement.

388 ii. For Notebooks, WOL may be automatically disabled when the product is disconnected from  
389 ac mains power.

390 iii. For all products with WOL, directed packet filters shall be enabled and set to an industry  
391 standard default configuration.

392 iv. Products that do not support Sleep Mode by default are only subject to the Display Sleep  
393 Mode requirement.

**Table 3: Power Management Requirements**

Mode or Mode Transition	Requirement	Desktops	Integrated Desktops	Portable All-In-Ones	Notebooks	Slates/Tablets	Thin Clients	Workstations
<b>System Sleep/Alternative Low Power Mode</b>	(1) Sleep/Alternative Low Power Mode shall be set to activate after no more than 30 minutes of user inactivity. (2) The speed of any active 1 Gb/s or faster Ethernet network links shall be reduced when transitioning to Sleep Mode or Off Mode. Or the links shall enter Energy Efficient Ethernet state when transitioning to Alternative Low Power Mode	Yes	Yes	Yes	Yes	N/A	Yes	Yes
<b>Display Sleep Mode</b>	(1) Display Sleep Mode shall be set to activate after no more than 15 minutes of user inactivity.	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Wake on LAN (WOL)</b>	(1) Computers with Ethernet capability shall provide users with an option to enable and disable WOL for Sleep Mode. (2) Computers with Ethernet capability that are shipped through enterprise channels shall either: (a) be shipped with WOL enabled by default for Sleep Mode, when the computer is operating on ac mains power; or (b) provide users with the ability to enable WOL that is accessible from both the client operating system user interface and over the network <sup>ii</sup> .	Yes	Yes	Yes	Yes	N/A	Yes	Yes
<b>Wake Management</b>	(1) Computers with Ethernet capability that are shipped through enterprise channels shall: (a) be capable of both remote (via network) and scheduled (via real-time clock) wake events from Sleep Mode, and (b) provide clients with the ability to centrally manage (via vendor tools) any wake management settings that are configured through hardware settings if the manufacturer has control over such features.	Yes	Yes	Yes	Yes	N/A	Yes	Yes

396 **3.4 User Information Requirements**

397 3.4.1 Products shall be shipped with informational materials to notify customers of the following:

- 398 i. A description of power management settings that have been enabled by default,
- 399 ii. A description of the timing settings for various power management features, and
- 400 iii. Instructions for properly waking the product from Sleep Mode.

401 3.4.2 Products shall be shipped with one or more of the following:

- 402 i. A list of default power management settings.
- 403 ii. A note stating that default power management settings have been selected for compliance  
404 with ENERGY STAR (within 15 min of user inactivity for the display, within 30 min for the  
405 computer, if applicable per Table 3), and are recommended by the ENERGY STAR program  
406 for optimal energy savings.
- 407 iii. Information about ENERGY STAR and the benefits of power management, to be located at  
408 or near the beginning of the hard copy or electronic user manual, or in a package or box  
409 insert.

410 3.4.3 Provisions 3.4.1 and 3.4.2 may be met through use of either electronic or printed product  
411 documentation, provided it adheres to all of the following:

- 412 i. Documentation is shipped with the product (e.g., in a printed manual or insert, on included  
413 optical media, in a file installed with the software load shipped to the customer) or available  
414 electronically on the manufacturer's website. In the latter case, instructions for accessing the  
415 information on the website shall be provided in the product package or on the Desktop or  
416 home screen; and
- 417 ii. Documentation is included either (a) only with ENERGY STAR certified Computers; or (b) as  
418 part of the standard documentation if and only if accompanied by EPA-approved customer  
419 guidance on how to identify if their computer configuration is ENERGY STAR certified.

420 **3.5 Requirements for Desktop, Integrated Desktop, and Notebook Computers**

421 3.5.1 Resume Time Requirement: Notebook computers are required to wake from sleep or an  
422 alternative low power mode with a latency of less than or equal to 5 seconds from initiation of  
423 wake event to system becoming fully usable including rendering of display. Desktop and  
424 Integrated Desktop Computers shall meet this same requirement, but with a latency of less than  
425 or equal to 10 seconds. Manufacturers shall self-declare that the product can meet this  
426 requirement<sup>iii</sup>.

427 3.5.2 Calculated Typical Energy Consumption ( $E_{TEC}$ ) for Desktop, Integrated Desktop, and Notebook  
428 Computers per Equation 1 shall be less than or equal to the maximum TEC requirement  
429 ( $E_{TEC\_MAX}$ ) per Note: As discussed with stakeholders as part of the Version 8 process as well as  
430 the Version 9 discussion guide, EPA has simplified and updated the notebook mode weightings  
431 to reflect current use patterns of notebooks based on an industry data set. This data set included  
432 data on millions of products and the new mode weightings were vetted during the Version 8  
433 development process. As proposed, Version 9 would also remove the Full Network Proxy mode  
434 weightings.

---

<sup>i</sup> Where Sleep Mode is supported by the UUT by default and Sleep Mode power is used as part of the TEC equation for qualification.

<sup>ii</sup> Option (b) is not permitted for systems that use WOL in order to meet the definition of Full Network Connectivity to claim the Full Capability mode weighting.

<sup>iii</sup> For purposes of ENERGY STAR third-party certification, these requirements shall not be reviewed when products are initially certified nor during subsequent verification testing. Rather, EPA reserves the right to request supporting documentation at any time. Resume time requirements do not apply to workstations or thin clients.

435 3.5.3 Equation 2, subject to the following requirements:

- 436 i. The Additional Internal Storage adder allowance ( $TEC_{STORAGE}$ ) shall be applied if there are  
437 more than one internal storage devices present in the product, in which case it shall only be  
438 applied once.
- 439 ii. The Integrated Display adder allowance ( $TEC_{INT\_DISPLAY}$ ) applies only for Integrated Desktops  
440 and Notebooks and may be applied for each display. For Enhanced-performance Integrated  
441 Displays, the adder is calculated as presented in Table 7 and Equation 3.

442 **Note:** EPA has removed the Full Network Connectivity mode weightings and incentives, as they would no  
443 longer be present with the proposed updated mode weightings.

- 444 iii. For Notebooks, Desktops, and Integrated Desktops that use an Alternative Low Power Mode  
445 in place of System Sleep Mode and Long Idle Mode, power in Alternative Low Power Mode  
446 ( $P_{ALPM}$ ) may be used in place of both the power in Sleep ( $P_{SLEEP}$ ) and the power in Long Idle  
447 ( $P_{LONG\_IDLE}$ ) in Equation 1 if the Alternative Low Power Mode measured power is less than or  
448 equal to 10 watts. In such instances, ( $P_{SLEEP} \times T_{SLEEP}$ ) and ( $P_{LONG\_IDLE} \times T_{LONG\_IDLE}$ )  
449 are replaced by ( $P_{ALPM} \times T_{SLEEP}$ ) and ( $P_{ALPM} \times T_{LONG\_IDLE}$ ); Equation 1 remains  
450 otherwise unchanged.

451 Notebooks, Desktops, and Integrated Desktops with switchable graphics may not apply the  
452 Discrete Graphics allowance,  $TEC_{GRAPHICS}$ , from Table 7 in **Note:** As discussed with stakeholders as part  
453 of the Version 8 process as well as the Version 9 discussion guide, EPA has simplified and updated the  
454 notebook mode weightings to reflect current use patterns of notebooks based on an industry data set.  
455 This data set included data on millions of products and the new mode weightings were vetted during the  
456 Version 8 development process. As proposed, Version 9 would also remove the Full Network Proxy mode  
457 weightings.

- 458 iv. Equation 2. However, for Desktop and Integrated Desktop systems that provide automated  
459 Switchable Graphics enabled by default, an allowance equal to 14.4 watts (Desktop or  
460 Integrated Desktop) may be applied. This capability is manufacturer-declared.

461 **Equation 1: TEC Calculation ( $E_{TEC}$ ) for Desktop, Integrated Desktop,  
462 and Notebook Computers**

463 
$$E_{TEC} = \frac{8760}{1000} \times (P_{OFF} \times T_{OFF} + P_{SLEEP} \times T_{SLEEP} + P_{LONG\_IDLE} \times T_{LONG\_IDLE}$$

464 
$$+ P_{SHORT\_IDLE} \times T_{SHORT\_IDLE})$$

465 *Where:*

- 466
  - 467  $P_{OFF}$  = Measured power consumption in Off Mode (W);
  - 468  $P_{SLEEP}$  = Measured power consumption in Sleep Mode (W);
  - 469  $P_{LONG\_IDLE}$  = Measured power consumption in Long Idle Mode (W);
  - 470  $P_{SHORT\_IDLE}$  = Measured power consumption in Short Idle Mode (W); and
  - 471  $T_{OFF}$ ,  $T_{SLEEP}$ ,  $T_{LONG\_IDLE}$ , and  $T_{SHORT\_IDLE}$  are mode weightings as  
472 specified in Table 4 (for Desktops, Integrated Desktops) or  
473 Table 5 (for Notebooks).
- 474

475

**Table 4: Mode Weightings for Desktops and Integrated Desktop Computers**

Mode Weighting	Conventional
T <sub>OFF</sub>	15%
T <sub>SLEEP</sub>	45%
T <sub>LONG_IDLE</sub>	10%
T <sub>SHORT_IDLE</sub>	30%

476

477

**Table 5: Mode Weightings for Notebook Computers**

Mode Weighting	Conventional
T <sub>OFF</sub>	10%
T <sub>SLEEP</sub>	60%
T <sub>LONG_IDLE</sub>	10%
T <sub>SHORT_IDLE</sub>	20%

478  
479  
480  
481  
482

**Note:** As discussed with stakeholders as part of the Version 8 process as well as the Version 9 discussion guide, EPA has simplified and updated the notebook mode weightings to reflect current use patterns of notebooks based on an industry data set. This data set included data on millions of products and the new mode weightings were vetted during the Version 8 development process. As proposed, Version 9 would also remove the Full Network Proxy mode weightings.

483

**Equation 2: E<sub>TEC\_MAX</sub> Calculation for Desktop, Integrated Desktop, and Notebook Computers**

484  
485

$$E_{TEC\_MAX} = (TEC_{BASE} + TEC_{MEMORY} + TEC_{GRAPHICS} + TEC_{STORAGE} + TEC_{INT\_DISPLAY} + TEC_{SWITCHABLE} + TEC_{MOBILEWORKSTATION} + TEC_{>1G\ to\ <10GLAN} + TEC_{10GLAN})$$

486  
487  
488  
489  
490  
491  
492  
493  
494  
495

Where:

- *TEC<sub>BASE</sub> is the Base allowance specified in Table 6; and,*
- *TEC<sub>GRAPHICS</sub> is the discrete graphics allowance as specified in Table 7, with the exception of systems with integrated graphics, which do not receive an allowance, or Desktops and Integrated Desktops with switchable graphics enabled by default, which receive an allowance through TEC<sub>SWITCHABLE</sub>; and*
- *TEC<sub>MEMORY</sub>, TEC<sub>STORAGE</sub>, TEC<sub>INT\_DISPLAY</sub>, TEC<sub>SWITCHABLE</sub>, TEC<sub>MOBILEWORKSTATION</sub>, TEC<sub>>1G to <10GLAN</sub> and TEC<sub>10GLAN</sub> are adder allowances as specified in Table 7.*

496

497  
498

**Note:** EPA proposes removal of the IPS efficiency allowance and ALPM full network proxy allowance from Version 9.

499

EPA proposes to remove the IPS efficiency allowance due to lack of use under Version 8.

500  
501  
502

The ALPM full network proxy allowance has been removed because EPA is no longer distinguishing products by their ability to maintain an ALPM. For similar reasons, references to ALPM and full network proxy have been removed in the notebook mode weightings above.

503 EPA has also simplified Equation 2 to account for the changes to Tables 6 and 7 below.

504

505 **Table 6: Base TEC ( $TEC_{BASE}$ ) Allowances for Notebooks, Desktops, and Integrated Desktops**

Category	Base Allowance
Notebook	2.0
Integrated Desktop	2.0
Desktop	15.0

506

507 **Note:** EPA has greatly simplified the base allowances for notebooks, desktops and integrated desktops in  
508 Version 9. After review of our data set, EPA concluded that performance is no longer a notable  
509 differentiator in whether products can achieve efficient low power operation when in idle / sleep modes.

510 As such, EPA has removed the previous p-score approach for all types of notebook and desktop products  
511 in Version 9. This simplification eliminates confusion surrounding evolving complex CPU chipsets and  
512 rewards products purely on their ability to power down effectively. EPA analyzed the data set across  
513 various “p-scores” using a composite p-score approach leveraging newer p-score data to account for  
514 multiple core types within a CPU and found that systems across the performance range from a variety of  
515 manufacturers in both notebooks and desktops could meet the new TEC requirements with these  
516 simplified performance agnostic base allowances.

517 These base allowances, combined with the functional adder allowance changes below, result in product  
518 pass rates of roughly 30% in each of the categories in Table 6 above, with coverage of products across a  
519 range of performance levels.

520

521

522 **Table 7: Functional Adder Allowances for Desktop, Integrated Desktop, Thin Client, and Notebook**  
 523 **Computers**

Function		Desktop	Integrated Desktop	Notebook
<b>TEC<sub>MEMORY</sub> (kWh)<sup>iv</sup></b>		$0.5 \times [1.7 + (0.24 \times GB)]$		N/A
<b>TEC<sub>GRAPHICS</sub> (kWh)<sup>v,vi</sup></b>		$29.4 \times \tanh(0.008 \times FB\_BW - 0.03) + 11 + (0.011 \times FB\_BW)$		$14.7 \times \tanh(0.008 \times FB\_BW - 0.03) + 5.5 + (0.0055 \times FB\_BW)$
<b>TEC<sub>SWITCHABLE</sub> (kWh)<sup>vii</sup></b>		14.4		N/A
<b>TEC<sub>STORAGE</sub> (kWh)<sup>viii</sup></b>	3.5" HDD	16.5		N/A
	2.5" HDD	2.1		
	Hybrid HDD/SSD	0.8		
	SSD (including M.2 port solutions)	0.4		
<b>TEC<sub>INT_DISPLAY</sub> (kWh)<sup>ix</sup></b>	$A < 190$	N/A	$[(3.43 \times r) + (0.148 \times A) + 1.30] \times (1 + EP)$	$8.76 \times 0.30 \times (1+EP) \times (0.43 \times r + 0.0263 \times A)$
	$190 \leq A < 210$		$[(3.43 \times r) + (0.018 \times A) + 26.1] \times (1 + EP)$	
	$210 \leq A < 315$		$[(3.43 \times r) + (0.078 \times A) + 13.2] \times (1 + EP)$	
	$A \geq 315$		$[(3.43 \times r) + (0.156 \times A) - 11.3] \times (1 + EP)$	
<b>TEC<sub>MOBILEWORKSTATION</sub> (kWh)<sup>x</sup></b>		N/A		4.0
<b>TEC<sub>&gt;1G to &lt;10GLAN</sub> (kWh)<sup>xi</sup></b>		4.0		N/A
<b>TEC<sub>10GLAN</sub> (kWh)<sup>xii</sup></b>		18.0		N/A

524

525 **Note:** In EPA's analysis of setting new TEC requirements, the Agency determined that a combination of  
 526 increased product efficiency and new notebook mode weightings created a situation in which maintaining  
 527 all Version 8 functional adders would result in a negative base allowance for notebooks. EPA found that  
 528 result counterintuitive, so EPA identified two notebook functional adders that were claimed in low  
 529 numbers and as such. EPA now proposes to remove the memory and storage adders from Table 7  
 530 above for notebooks. EPA has expanded the base allowance in consideration of the proposed removal of  
 531 the above adders.

- iv **TEC<sub>MEMORY</sub> Adder:** GB applies per GB installed in the system.
- v **TEC<sub>GRAPHICS</sub> Adder:** Applies to only the first dGfx installed in the system, but not Switchable Graphics.
- vi **FB\_BW:** Is the display frame buffer bandwidth in gigabytes per second (GB/s). This is a manufacturer declared parameter and should be calculated as follows: (Data Rate [Mhz] × Frame Buffer Data Width [bits]) / (8 × 1000)
- vii **TEC<sub>SWITCHABLE</sub> Incentive:** Applies to automated switching that is enabled by default in Desktops and Integrated Desktops.
- viii **TEC<sub>STORAGE</sub> Adder:** Applies once if system has an Additional Internal Storage device.
- ix **TEC<sub>INT\_DISPLAY</sub> Adder:** EP is the Enhanced Performance Display allowance calculated per Equation 3; r is the Screen resolution in megapixels; and A is viewable screen area in square inches. This adder may be applied for each display if there are multiple displays in the system which are enabled as-shipped and in testing.
- x **TEC<sub>MOBILEWORKSTATION</sub> Adder:** Applies once if the system meets the full Mobile Workstation definition in Section 1.
- xi **TEC<sub>>1G to <10GLAN</sub> Adder:** Applies once if system contains an Ethernet port with rated throughput greater than 1Gb/s but less than 10 Gb/s.
- xii **TEC<sub>10GLAN</sub> Adder:** Applies once if the system contains a 10 Gb/s Ethernet port.



532 For desktops, EPA has largely maintained the existing functional adders from Version 8 though EPA has  
 533 halved the size of the memory adder for similar reasons to the notebooks above to ensure that the  
 534 integrated desktops maintained a positive base allowance. This has been factored into the base  
 535 allowances for both desktops and integrated desktops.

536 Finally, based on stakeholder feedback, the discrete graphics adders for both notebooks and desktops  
 537 now align with their respective CEC Tier 2 discrete graphics adder values.

538 **Equation 3: Calculation of Allowance for Enhanced-performance Integrated Displays**

$$539 \quad EP = \begin{cases} 0, & \text{No Enhanced Performance Display} \\ 0.3, & \text{Enhanced Performance Display, } d < 27 \\ 0.75, & \text{Enhanced Performance Display, } d \geq 27 \end{cases}$$

540 *Where:*

- 541 ▪ *d is the diagonal of the screen, in inches*

542 **3.6 Requirements for Slates/Tablets and Portable All-In-One Computers**

543 3.6.1 Slates/Tablets and Portable All-In-One Computers shall follow **all** of the requirements for  
 544 Notebook Computers in Section 3.5 above, including calculations of the following:

- 545 i. Calculated Typical Energy Consumption ( $E_{TEC}$ ), using Equation 1 with the Notebook  
 546 Computer Mode Weightings from Table 5.
- 547 ii. Calculated Maximum Allowed Typical Energy Consumption ( $E_{TEC\_MAX}$ ), using Equation 2 with  
 548 the appropriate base Notebook Computer allowance from Table 6, and applicable Notebook  
 549 Computer functional adder allowances from Table 7.

550 **3.7 Requirements for Workstations**

551 **Note:** EPA is still interested in referencing a more modern and relevant active state workstation  
 552 benchmark in Version 9 but at this point is still lacking data and supporting information from stakeholders  
 553 on newer benchmark progress and how we can best adopt those measurements going forward. EPA  
 554 would appreciate additional stakeholder feedback to aid EPA in identifying the best modern workstation  
 555 benchmark to reference in Section 3.7.2 below for potential inclusion in the Draft 2 specification.

556  
 557 3.7.1 Weighted power consumption ( $P_{TEC}$ ) as calculated per Equation 4 shall be less than or equal to  
 558 the maximum weighted power consumption requirement ( $P_{TEC\_MAX}$ ) as calculated per Equation 5.

559 **Equation 4:  $P_{TEC}$  Calculation for Workstations**

$$560 \quad P_{TEC} = P_{OFF} \times T_{OFF} + P_{SLEEP} \times T_{SLEEP} + P_{LONG\_IDLE} \times T_{LONG\_IDLE} \\ 561 \quad + P_{SHORT\_IDLE} \times T_{SHORT\_IDLE}$$

562 *Where:*

- 563 ▪  $P_{OFF}$  = Measured power consumption in Off Mode (W);
- 564 ▪  $P_{SLEEP}$  = Measured power consumption in Sleep Mode (W);
- 565 ▪  $P_{LONG\_IDLE}$  = Measured power consumption in Long Idle Mode  
 566 (W);
- 567 ▪  $P_{SHORT\_IDLE}$  = Measured power consumption in Short Idle Mode  
 568 (W); and
- 569 ▪  $T_{OFF}$ ,  $T_{SLEEP}$ ,  $T_{LONG\_IDLE}$ , and  $T_{SHORT\_IDLE}$  are mode weightings as  
 570 specified in Table 8.

571

**Table 8: Mode Weightings for Workstations**

T <sub>OFF</sub>	T <sub>SLEEP</sub>	T <sub>LONG_IDLE</sub>	T <sub>SHORT_IDLE</sub>
10%	35%	20%	35%

572

573

**Equation 5: P<sub>TEC\_MAX</sub> Calculation for Workstations**

574

$$P_{TEC\_MAX} = 0.28 \times (P_{MAX} + N_{HDD} \times 5)$$

575

Where:

576

▪ P<sub>MAX</sub> = Measured maximum power consumption (W)

577

▪ N<sub>HDD</sub> = Number of installed hard disk drives (HDD) or solid-state drives (SSD)

578

579 3.7.2 Active State Benchmark: To be ENERGY STAR certified, a Workstation must be submitted for  
580 certification with the following information disclosed in full:

581 i. LINPAC benchmark test results, compiler optimizations, and total energy consumed over the  
582 duration of the test; and

583 ii. SPECviewperf benchmark test results, configuration options, total duration of the test, and  
584 total energy consumed over the duration of the test.

585 3.7.3 Desktop Workstations: Products marketed as workstations may be ENERGY STAR certified  
586 under the Desktop requirements in Section 3.5 instead of the Workstation requirements in  
587 Section 3.7, at the Partner’s option. EPA will identify Workstations certified as Desktops as  
588 “Desktops” in all ENERGY STAR marketing materials, on certified product lists, etc.

### 589 3.8 Requirements for Thin Clients

590 3.8.1 Calculated Typical Energy Consumption (E<sub>TEC</sub>) per Equation 1 shall be less than or equal to the  
591 Maximum TEC Requirement (E<sub>TEC\_MAX</sub>), as calculated per Equation 6, subject to the following  
592 requirements.

593 i. Allowances can only be applied if the corresponding adders are enabled by default.

594 ii. Thin Clients shall utilize the mode weightings in Table 9 when calculating E<sub>TEC</sub>.

595 iii. For Thin Clients that lack a discrete System Sleep Mode, Long Idle State power (P<sub>LONG\_IDLE</sub>)  
596 may be used in place of Sleep Mode Power (P<sub>SLEEP</sub>) in Equation 1 so long as the system  
597 meets the Thin Client TEC allowance. In such instances, (P<sub>SLEEP</sub> × T<sub>SLEEP</sub>), is replaced by  
598 (P<sub>LONG\_IDLE</sub> × T<sub>SLEEP</sub>); Equation 1 remains otherwise unchanged.

599

600

**Table 9: Mode Weightings for Thin Clients**

T <sub>OFF</sub>	T <sub>SLEEP</sub>	T <sub>LONG_IDLE</sub>	T <sub>SHORT_IDLE</sub>
45%	5%	15%	35%

601

**Equation 10: Calculation of E<sub>TEC\_MAX</sub> for Thin Clients**

602

$$E_{TEC\_MAX} = TEC_{BASE} + TEC_{GRAPHICS} + TEC_{WOL} + TEC_{INT\_DISPLAY}$$

603 Where:

- 604 ▪ *TEC<sub>BASE</sub> is the Base Allowance specified in Table*
- 605 *Table 11;*
- 606 ▪ *TEC<sub>GRAPHICS</sub> is the Discrete Graphics allowance specified in*
- 607 *Table 11 if applicable;*
- 608 ▪ *TEC<sub>WOL</sub> is the Wake-on-LAN allowance specified in Table*
- 609 *Table 11 if applicable;*
- 610 ▪ *TEC<sub>INT\_DISPLAY</sub> is the Integrated Display allowance for Integrated*
- 611 *Desktops specified in Table 7 if applicable; and*

612 **Table 11: Adder Allowances for Thin Clients**

Adder	Allowance (kWh)
TEC <sub>BASE</sub>	31
TEC <sub>GRAPHICS</sub>	36
TEC <sub>WOL</sub>	2

613

614

615 **Note:** Products intended for sale in the US market are subject to minimum toxicity and recyclability

616 requirements. Please see ENERGY STAR® Program Requirements for Computers: Partner Commitments

617 for details.

## 618 4 TESTING

### 619 4.1 Test Methods

620 4.1.1 When testing Computer products, the test methods identified in Table 12 shall be used to

621 determine ENERGY STAR certification.

622 **Table 12: Test Methods for ENERGY STAR Certification**

Product Type or Component	Test Method
All	ENERGY STAR Draft Test Method for Computers, Rev. October 2019

### 623 4.2 Number of Units Required for Testing

624 4.2.1 Representative Models shall be selected for testing per the following requirements:

- 625 i. For certification of an individual product configuration, the unique configuration that is
- 626 intended to be marketed and labeled as ENERGY STAR is considered the Representative
- 627 Model.
- 628 ii. For certification of a Product Family of all product types, with the exception of Workstations,
- 629 product configurations that represent the worst-case power consumption for each product
- 630 category within the family are considered Representative Models. When submitting Product
- 631 Families, manufacturers continue to be held accountable for any efficiency claims made
- 632 about their products, including those not tested or for which data were not reported. This
- 633 includes ensuring that all models shipped as ENERGY STAR certified within the product
- 634 family maintain the same power management settings when testing the Representative
- 635 Model(s).

636 4.2.2 Note: EPA has removed the language which was previously labeled subsection 4.2.1.iii from  
637 Version 8 which covered systems that met multiple performance categories and how those  
638 should be tested and certified, as EPA has proposed the removal of performance categories in  
639 the Version 9 specification. For certification of a Product Family of Workstations under the  
640 Workstation or Desktop product type, the product configuration that represents the worst-case  
641 power consumption with a single GPU within the family is considered the Representative Model.  
642

643 Note: Workstations that meet ENERGY STAR requirements with a single graphics device may  
644 also have a configuration with more than one graphics device be ENERGY STAR certified,  
645 provided the additional hardware configuration is identical with the exception of the additional  
646 graphics device(s). The use of multiple graphics includes, but is not limited to, driving multiple  
647 displays and ganging for high performance, multi-GPU configurations (e.g. ATI Crossfire, NVIDIA  
648 SLI). In such cases, and until such time as SPECviewperf® supports multiple graphics threads,  
649 manufacturers may submit the test data for the workstation with the single graphics device for  
650 both configurations without retesting the system

651 4.2.3 A single unit of each Representative Model shall be selected for testing.

652 4.2.4 All units/configurations for which a Partner is seeking ENERGY STAR certification, must meet the  
653 ENERGY STAR requirements. However, if a Partner wishes to certify configurations of a model  
654 for which non-ENERGY STAR certified alternative configurations exist, the Partner must assign  
655 the certified configurations an identifier in the model name/number that is unique to ENERGY  
656 STAR certified configurations. This identifier must be used consistently in association with the  
657 certified configurations in marketing/sales materials and on the ENERGY STAR list of certified  
658 products (e.g. model A1234 for baseline configurations and A1234-ES for ENERGY STAR  
659 certified configurations).

660 **Note:** There may be cases—as described in the paragraph above—where not all  
661 units/configurations will meet ENERGY STAR requirements. If so, the worst-case configuration  
662 for test will be the worst-case certified configuration, and not one of the presumably even higher-  
663 energy consuming non-certified configurations.

### 664 4.3 International Market Certification

665 4.3.1 Products shall be tested for certification at the relevant input voltage/frequency combination for  
666 each market in which they will be sold and promoted as ENERGY STAR.

667 **Note:** Partner must ensure that all configurations certified as ENERGY STAR continue to meet  
668 the certification criteria through subsequent firmware, software, or other changes to the certified  
669 product.

670 **Note:** EPA has added a permanent note specifying that all products must continue to meet ENERGY  
671 STAR requirements regardless of future firmware, software or other changes to the certified product that  
672 originate from the partner.

### 673 4.4 Customer Software and Management Service Pre-Provisioning

674 4.4.1 If a manufacturing Partner is hired by a customer to load a custom image on an ENERGY STAR  
675 certified computer, the Partner shall take the following steps:

676 i. Inform the customer that their product may not meet ENERGY STAR with the custom image.  
677 A sample notification letter is available on the ENERGY STAR Web site.

678 ii. Encourage the customer to test the product for ENERGY STAR compliance.

679 iii. Encourage the customer, should the product no longer meet ENERGY STAR, to make use of  
680 EPA's free technical assistance that can assist with Power Management performance, which  
681 can be found at [www.energystar.gov/fedofficeenergy](http://www.energystar.gov/fedofficeenergy).

682 **5 USER INTERFACE**

683 5.1.1 Manufacturers are encouraged to design products in accordance with the user interface standard  
684 IEEE 1621: Standard for User Interface Elements in Power Control of Electronic Devices  
685 Employed in Office/Consumer Environments. For details, see <http://eetd.LBL.gov/Controls>.

686 **6 EFFECTIVE DATE**

687 6.1.1 Effective Date: The Version 9 ENERGY STAR Computers specification shall take effect on TBD.  
688 To be ENERGY STAR certified, a product model shall meet the ENERGY STAR specification in  
689 effect on its date of manufacture. The date of manufacture is specific to each unit and is the date  
690 on which a unit is considered to be completely assembled.

691 **Note:** EPA intends to finalize the Version 9 specification in Q2 of 2024 with a TBD effective date  
692 sometime in Q1 2025, nine months following the finalization of the specification.

693 6.1.2 Future Specification Revisions: EPA reserves the right to change this specification should  
694 technological and/or market changes affect its usefulness to consumers, industry, or the  
695 environment. In keeping with current policy, revisions to the specification are arrived at through  
696 stakeholder discussions. In the event of a specification revision, please note that the ENERGY  
697 STAR certification is not automatically granted for the life of a product model.

698 **7 CONSIDERATIONS FOR FUTURE REVISIONS**

699 7.1.1 **Active Mode**: EPA will continue to monitor developments in test methodology that addresses  
700 active mode, where the computer is actively performing tasks, and assess whether these  
701 measurements warrant inclusion into the ENERGY STAR Computers specification.