



United States
ENVIRONMENTAL PROTECTION AGENCY

Washington, D.C. 20460

ENERGY STAR Ventilating Fan Partner
Unit Shipment Data
Office of Atmospheric Programs

NAME OF MANUFACTURER: _____

DATE OF SUBMISSION: _____

SUBMITTED BY (NAME): _____

PLEASE LIST ANY UNAFFILIATED PRIVATE LABELERS THAT REBRAND YOUR PRODUCTS: _____

Below, only report shipments to consumers or retailers. Do not include business to business shipments (shipments to unaffiliated private labelers). If you ONLY ship to private labelers, indicate zero shipments and list private labelers selling in the U.S. marketplace on the line above.

Reporting Period: CALENDAR YEAR 2008 (JAN. TO DEC.)

Ventilating Fan ¹ Product Type	ENERGY STAR [®] U.S. Unit Shipments to Consumers or Retailers (REQUIRED)	Total U.S. Unit Shipments to Consumers or Retailers (ENERGY STAR + Non-ENERGY STAR) (REQUESTED)
Range Hoods - up to 500 cfm (max)		
Bathroom and Utility Room Fans - 10 to 80 cfm		
Bathroom and Utility Room Fans - 90 to 130 cfm		
Bathroom and Utility Room Fans - 140 to 500 cfm (max)		
In-Line Ventilating Fans - single-port ²		
In-Line Ventilating Fans - multi-port ³		
Total	0	0

Submission Deadline: February 27, 2009
Deadline to Avoid Partnership Termination: March 31, 2009

Please submit by mail, email, or fax to:
Elliott Rector
ICF International
1725 Eye Street, NW
Suite 1000
Washington, DC 20006
unitshipmentdata@icfi.com
Fax: (202) 862-1144

DEFINITIONS

¹ A ceiling, wall-mounted, or remotely mounted in-line fan designed to be used in a bathroom or utility room, or a kitchen range hood, whose purpose is to move objectionable air from inside the building to the outdoors. Residential ventilating fans used for cooling (e.g., whole-house fans) or air circulation are excluded. Heat/energy recovery ventilation fans ducted to the ventilated space, powered attic ventilators (e.g., gable fans), residential ventilating fans with heat lamps are excluded. This definition does not address passive ventilation of any kind.

^{2, 3} A fan designed to be located within the building structure and requires ductwork on both intake and exhaust. Those inline fans with only one intake are referred to as "single port" in-line fans, while those with multiple intake ports are referred to as "multi-port" in-line fans.

EPA plans to use the data only for program evaluations. EPA will release this information only as aggregated data and only to the extent required by law.

The public reporting and recordkeeping burden for this collection of information is estimated to average 6.69 hours per response. Send comments on the Agency's need for this information, the accuracy of the provided burden estimates, and any suggested methods for minimizing respondent burden, including through the use of automated collection techniques to the Director, Collection Strategies Division, U.S. Environmental Protection Agency (2822T), 1200 Pennsylvania Ave., NW, Washington, D.C. 20460. Include the OMB control number in any correspondence. Do not send the completed form to this address.