



ENERGY STAR® Program Requirements Product Specification for Imaging Equipment

Test Method for Determining Imaging Equipment Energy Use Version 2.0 – Final Draft Rev. Feb-2012

1 OVERVIEW

The following test method shall be used for determining product compliance with requirements in the ENERGY STAR Eligibility Criteria for Imaging Equipment.

Note: This document contains proposed changes to the ENERGY STAR test methods for both Operational Mode (OM) and Typical Energy Consumption (TEC) imaging equipment products. The proposed changes incorporate the feedback received during and after the imaging equipment webinars held on April 13, 2011, August 4, 2011, and December 8, 2011. The U.S. Department of Energy (DOE) and the U.S. Environmental Protection Agency (EPA) thank all stakeholders who participated and provided feedback and welcome additional comments on the changes outlined below.

Please note that significant changes are proposed for the network connections used in the OM and TEC test methods; only one network connection is to be used for the test, and the network connection order of preference is specified in Table 6, below. These changes may invalidate at least 57% of OM product data used during the development of the revised Version 2.0 specification as the energy consumption will be different when measured according to the revised test method. On the other hand, the changes proposed to the TEC test method should affect few products as most were tested using a single Ethernet connection, the primary connection specified in Table 6.

2 APPLICABILITY

ENERGY STAR test requirements are dependent upon the feature set of the products under evaluation.

Table 1: Test Procedure Applicability

Product Type	Media Format	Marking Technology	ENERGY STAR Evaluation Method
Copier	Standard	Direct Thermal (DT), Dye Sublimation (DS), Electro-photographic (EP), Solid Ink (SI), Thermal Transfer (TT)	Typical Energy Consumption (TEC)
	Large	DT, DS, EP, SI, TT	Operational Mode (OM)
Digital Duplicator	Standard	Stencil	TEC
Fax Machine	Standard	DT, DS, EP, SI, TT	TEC
		Ink Jet (IJ)	OM
Mailing Machine	All	DT, EP, IJ, TT	OM
Multifunction Device (MFD)	Standard	High Performance IJ, DT, DS, EP, SI, TT	TEC
		IJ, Impact	OM
	Large	DT, DS, EP, IJ, SI, TT	OM

Product Type	Media Format	Marking Technology	ENERGY STAR Evaluation Method
Printer	Standard	High Performance IJ, DT, DS, EP, SI, TT	TEC
		IJ, Impact	OM
	Large or Small	DT, DS, EP, Impact, IJ, SI, TT	OM
	Small	High Performance IJ	TEC
Scanner	All	N/A	OM

21 shall be used to determine the applicability of each section of this document.

22 **Table 1: Test Procedure Applicability**

Product Type	Media Format	Marking Technology	ENERGY STAR Evaluation Method
Copier	Standard	Direct Thermal (DT), Dye Sublimation (DS), Electro-photographic (EP), Solid Ink (SI), Thermal Transfer (TT)	Typical Energy Consumption (TEC)
	Large	DT, DS, EP, SI, TT	Operational Mode (OM)
Digital Duplicator	Standard	Stencil	TEC
Fax Machine	Standard	DT, DS, EP, SI, TT	TEC
		Ink Jet (IJ)	OM
Mailing Machine	All	DT, EP, IJ, TT	OM
Multifunction Device (MFD)	Standard	High Performance IJ, DT, DS, EP, SI, TT	TEC
		IJ, Impact	OM
	Large	DT, DS, EP, IJ, SI, TT	OM
Printer	Standard	High Performance IJ, DT, DS, EP, SI, TT	TEC
		IJ, Impact	OM
	Large or Small	DT, DS, EP, Impact, IJ, SI, TT	OM
	Small	High Performance IJ	TEC
Scanner	All	N/A	OM

23 3 DEFINITIONS

24 Unless otherwise specified, all terms used in this document are consistent with the definitions in the
 25 ENERGY STAR Eligibility Criteria for Imaging Equipment.

26 4 TEST SETUP

27 4.1 General Test Setup

28 A) Test Setup and Instrumentation: Test setup and instrumentation for all portions of this procedure shall
 29 be in accordance with the requirements of International Electrotechnical Commission (IEC) Standard
 30 62301, Ed. 2.0, "Measurement of Household Appliance Standby Power", Section 4, "General
 31 Conditions for Measurements." In the event of conflicting requirements, the ENERGY STAR test
 32 method shall take precedence.

- 33 B) Ac Input Power: Products intended to be powered from an ac mains power source shall be connected
 34 to a voltage source appropriate for the intended market, as specified in Table 2 or Table 3.
- 35 1) Products shipped with external power supplies (EPSs) shall first be connected to the EPS and
 36 then to the voltage source specified in Table 2 or Table 3.
- 37 2) If a product is designed to operate at a voltage/frequency combination in a specific market that is
 38 different from the voltage/frequency combination for that market (e.g., 230 volts (V), 60 hertz (Hz)
 39 in North America), the manufacturer should test the product at the regional combination that most
 40 closely matches the product's design capabilities and note this on the test reporting sheet.

41 **Table 2: Input Power Requirements for Products with**
 42 **Nameplate Rated Power Less Than or Equal to 1500 W**

Market	Voltage	Voltage Tolerance	Maximum Total Harmonic Distortion	Frequency	Frequency Tolerance
North America, Taiwan	115 V ac	+/- 1.0 %	2.0 %	60 Hz	+/- 1.0 %
Europe, Australia, New Zealand	230 V ac	+/- 1.0 %	2.0 %	50 Hz	+/- 1.0 %
Japan	100 V ac	+/- 1.0 %	2.0 %	50 Hz/60 Hz	+/- 1.0 %

43
 44 **Table 3: Input Power Requirements for Products with**
 45 **Nameplate Rated Power Greater than 1500 W**

Market	Voltage	Voltage Tolerance	Maximum Total Harmonic Distortion	Frequency	Frequency Tolerance
North America, Taiwan	115 V ac	+/- 4.0 %	5.0 %	60 Hz	+/- 1.0 %
Europe, Australia, New Zealand	230 V ac	+/- 4.0 %	5.0 %	50 Hz	+/- 1.0 %
Japan	100 V ac	+/- 4.0 %	5.0 %	50 Hz/60 Hz	+/- 1.0 %

- 46
- 47 C) Low-voltage Dc Input Power:
- 48 1) Products may be powered with a low-voltage dc source (e.g., via network or data connection)
 49 only if the dc source is the only acceptable source of power for the product (i.e., no ac plug or
 50 EPS is available).
- 51 2) Products powered by low-voltage dc shall be configured with an ac source of the dc power for
 52 testing (e.g., an ac-powered universal serial bus (USB) hub).
- 53 a) The ac source of the dc power used for testing shall be recorded and reported for all tests.
- 54 3) Power for the unit under test (UUT) shall include the following, as measured per Section 5 of this
 55 method:
- 56 a) Ac power consumption of the low-voltage dc source with the UUT as the load (P_L); and
 57 b) Ac power consumption of the low-voltage dc source with no load (P_S).
- 58 D) Ambient Temperature: Ambient temperature shall be $23^{\circ}\text{C} \pm 5^{\circ}\text{C}$.

- 59 E) Relative Humidity: Relative humidity shall be between 10% and 80%.
- 60 F) Power Meter: Power meters shall possess the following attributes:
- 61 1) Minimum Frequency Response: 3.0 kHz
- 62 2) Minimum Resolution:
- 63 a) 0.01 W for measurement values less than 10 W;
- 64 b) 0.1 W for measurement values from 10 W to 100 W;
- 65 c) 1 W for measurement values from 100 W to 1.5 kW; and
- 66 d) 10 W for measurement values greater than 1.5 kW.
- 67 e) Measurements of accumulated energy should have resolutions which are generally
- 68 consistent with these values when converted to average power. For accumulated energy
- 69 measurements, the figure of merit for determining required accuracy is the maximum power
- 70 value during the measurement period, not the average, since it is the maximum that
- 71 determines the metering equipment and setup.
- 72 G) Measurement Uncertainty:
- 73 1) Measurements of greater than or equal to 0.5 W shall have an uncertainty of 2% or better at the
- 74 95% confidence level.
- 75 2) Measurements of less than 0.5 W shall have an uncertainty of 0.02 W or better at the 95%
- 76 confidence level.
- 77 **Note:** In response to stakeholder comment, DOE expects the uncertainty measurements to be
- 78 implemented as part of the normal annual calibration check on the relevant measuring instruments, and
- 79 no uncertainty measurements need be taken during testing.
- 80 H) Time Measurement: Time measurements may be performed with a standard stopwatch or other time
- 81 keeping device with a resolution of at least 1 second.
- 82 I) Paper Specifications:
- 83 1) Standard Format products shall be tested in accordance with Table 4.
- 84 2) Large, Small, and Continuous Format products shall be tested using any compatible paper size.

85 **Table 4: Paper Size and Weight Requirements**

Market	Paper Size	Basis Weight (g/m ²)
North America / Taiwan	8.5" x 11"	75
Europe / Australia / New Zealand	A4	80
Japan	A4	64

86 **5 LOW-VOLTAGE DC SOURCE MEASUREMENT FOR ALL**

87 **PRODUCTS**

88

- 89 1) Connect the dc source to the power meter and relevant ac supply as specified in Table 2.
- 90
- 91 2) Verify that the dc source is unloaded.
- 92
- 93 3) Allow the dc source to stabilize for a minimum of 30 minutes.
- 94

95 4) Measure and record the unloaded dc source power (P_s) according to section 9.1.A.1 of this test
 96 method.

97 6 PRE-TEST UUT CONFIGURATION FOR ALL PRODUCTS

98 6.1 General Configuration

99 A) Product Speed for Calculations and Reporting: The product speed for all calculations and reporting
 100 shall be the highest speed as claimed by the manufacturer per the following criteria, expressed in
 101 images per minute (ipm) and rounded to the nearest integer:

- 102 1) In general, for Standard-size products, a single A4 or 8.5" x 11" sheet printed/copied/scanned on
 103 one side in one minute is equal to 1 (ipm).
- 104 a) When operating in duplex mode a single A4 or 8.5" x 11" sheet printed/copied/scanned on
 105 both sides in one minute is equal to 2 (ipm).
- 106 2) For all products, the product speed shall be based on:
- 107 a) The manufacturer-claimed print speed, unless the product cannot print, in which case,
 108 b) The manufacturer-claimed copy speed, unless the product cannot print or copy, in which
 109 case,
 110 c) The manufacturer-claimed scan speed.
- 111 3) For non-Continuous Form products, with the exception of mailing machines, the product speed
 112 shall be calculated per Table 5. If the maximum claimed speeds differ when producing images on
 113 different sizes of paper (e.g., A4 versus 8.5" x 11"), the highest speed shall be used.

114 **Table 5: Calculation of Product Speed for Standard, Small, and Large Format Products with the**
 115 **Exception of Mailing Machines**

Media Format	Media Size	Product Speed, s (ipm)
		Where: <ul style="list-style-type: none"> • s_P is the maximum claimed monochrome speed in pages per minute when processing the given media, • w is the width of the media, in meters (m), • ℓ is the length of the media, in meters (m).
Standard	8.5" x 11"	s_P
	A4	s_P
Small	4" x 6"	$0.25 \times s_P$
	A6	$0.25 \times s_P$
	Smaller than A6 or 4" x 6"	$16 \times w \times \ell \times s_P$
Large	A2	$4 \times s_P$
	A0	$16 \times s_P$

116
 117 4) For Continuous Form products, product speed shall be calculated per Equation 1

118 Equation 1: Calculation of Product Speed

119
$$s = 16 \times w \times s_L$$

148

149

Table 6: Network or Data Connections for Use in Test

Order of Preference for Use in Test (if Provided by UUT)	Connections for all Products
1	Ethernet – 1 Gb/s
2	Ethernet – 100/10 Mb/s
3	USB 3.x
4	USB 2.x
5	USB 1.x
6	RS232
7	IEEE 1284 ¹
8	Wi-Fi
9	Other Wired – in order of preference from highest to lowest speed
10	Other Wireless – in order of preference from highest to lowest speed
11	If none of the above, test with whatever connection is provided by the device (or none)

150

151

152

Note: DOE and EPA are proposing not to provide allowances for functional adders that are not active during testing, such as data and network connections other than those selected according to Table 6, above. DOE and EPA welcome comments on this proposed approach.

153

154

155

3) Products connected to Ethernet, per paragraph 6.1.C)2) above, and capable of supporting Energy Efficient Ethernet (IEEE Standard 802.3az)², shall be connected to a network switch or router that also supports Energy Efficient Ethernet for the duration of the test.

156

4) In all cases the type of connection used during the test shall be reported.

157

158

D) Service/Maintenance Modes: UUTs shall never be in service/maintenance modes, including color calibration, during testing.

159

a) Service/Maintenance modes shall be disabled prior to testing.

160

161

162

b) Manufacturers shall provide instructions detailing how to disable service/maintenance modes if this information is not included in the product documentation packaged with the UUT or is not readily available online.

¹ Also referred to as a Parallel or Centronics interface.

² Institute of Electrical and Electronics Engineers (IEEE) Standard 802.3az-2010. "IEEE Standard for Information Technology—Telecommunications and Information Exchange Between Systems—Local and Metropolitan Area Networks—Specific Requirements—Part 3: Carrier Sense Multiple Access with Collision Detection (CSMA/CD) Access Method and Physical Layer Specifications." 2010.

163 c) If service/maintenance modes cannot be disabled and a service/maintenance mode occurs
164 during a job other than the first job, the results from the job with the service/maintenance
165 mode may be replaced with results from a substitute job. In this case, the substitute job shall
166 be inserted into the test procedure immediately following Job 4. Each job period shall be 15
167 minutes.

168 **6.2 Configuration for Fax Machines**

169 A) All fax machines and products incorporating fax machines that connect to a telephone line shall be
170 connected to a telephone line during the test, in addition to the network connection specified by Table
171 6 if the UUT is network capable.

172 1) In the case that a working phone line is not available, a line simulator may be used as a
173 replacement.

174 B) Fax machines shall be tested with one image per job.

175 **6.3 Configuration for Digital Duplicators**

176 A) Except as noted below, digital duplicators shall be configured and tested as printers, copiers, or
177 MFDs, depending on their capabilities as-shipped.

178 1) Digital duplicators shall be tested at maximum claimed speed, which is also the speed that should
179 be used to determine the job size for performing the test, not at the default as-shipped speed, if
180 different.

181 2) For digital duplicators, there shall be only one original image.

182 **7 PRE-TEST UUT INITIALIZATION FOR ALL PRODUCTS**

183 **7.1 General Initialization**

184 A) Prior to the start of testing, the UUT shall be initialized as follows:

185 1) Set up the UUT per the instructions in the Manufacturer's Instructions or documentation.

186 a) Accessories, such as paper source, that are intended to be installed or attached by the end-
187 user shall be installed. Paper shall be placed in all paper sources designated to hold the
188 paper specified for testing, and the UUT shall pull from the default paper source.

189 b) If the product is connected to a computer, either directly or via a network, during the test, the
190 computer shall be running the newest version of the manufacturer's default driver available at
191 the time of testing using settings corresponding to the default settings upon shipment, unless
192 otherwise specified in this test method. The print driver version used for testing shall be
193 recorded.

194 i) In the event that a setting does not have a default and is not defined in this test method,
195 the setting shall be set according to the tester's discretion and shall be recorded.

196 ii) When connecting via a network and multiple computers are connected to the network,
197 print driver settings apply only to the computer sending the print jobs to the UUT.

198 **Note:** DOE clarified that print driver settings apply whether the computer and UUT are connected directly
199 or via a network to ensure that all testing is performed in the same manner.

200

201 DOE has also included clarification that only the computer actively sending jobs to the UUT must follow
202 these requirements. DOE requests feedback on how other computers connected to the network may
203 affect the UUT if not running the same print drivers.

204 c) For products designed to operate on battery power when not connected to the mains power
205 source, the battery shall be removed for all tests. For UUTs where operation without a battery
206 pack is not a supported configuration, the test shall be performed with fully charged battery
207 pack(s) installed, making sure to report this configuration in the test results. To ensure the
208 battery is fully charged, perform the following steps:

209

210 i) For UUTs that have an indicator to show that the battery is fully charged, continue
211 charging for an additional 5 hours after the indication is present.

212 ii) If there is no charge indicator, but the manufacturer's instructions provide a time estimate
213 for when charging this battery or this capacity of battery should be complete, continue
214 charging for an additional 5 hours after the manufacturer's indication.

215 iii) If there is no indicator and no time estimate in the instructions, but the charging current is
216 stated on the UUT or in the instructions, terminate charging 1 hour after the calculated
217 test duration or, if none of the above applies, the duration shall be 24 hours.

218 2) Connect the UUT to its power source.

219 3) Power on the UUT and perform initial system configuration, as applicable. Verify that default
220 delay times are configured according to product specifications and/or manufacturer
221 recommendations.

222 a) Product Speed for Testing: The product shall be tested with speed settings in their default as-
223 shipped configuration.

224 a) Auto-off for TEC Products: If a printer, digital duplicator, fax machine, or MFD with print-
225 capability has Auto-off capability and it is enabled as-shipped, it shall be disabled prior to
226 testing.

227 b) Auto-off for OM Products: If a product has an Auto-off Mode enabled as-shipped, it shall
228 remain enabled for the duration of testing.

229 4) User-controllable anti-humidity features shall be turned off or disabled for the duration of testing.

230 5) Pre-conditioning: Place the UUT in Off Mode, then let the UUT sit idle for 15 minutes.

231 a) For EP products, let the UUT sit in Off Mode for an additional 105 minutes, for a total of 120
232 minutes (2 hours).

233 b) Pre-conditioning is only required prior to beginning the first test on each UUT.

234 **8 TYPICAL ENERGY CONSUMPTION (TEC) TEST PROCEDURE**

235 **8.1 Job Structure**

236 A) Jobs per Day: The number of jobs per day (N_{JOBS}) is specified in Table 7.

237

Table 7: Number of Jobs per Day (N_{JOBS})

Monochrome Product Speed, s (ipm)	Jobs per Day (N _{JOBS})
s ≤ 8	8
8 < s < 32	s
s ≥ 32	32

238

239 B) Images per Job: Except for fax machines, the number of images shall be computed according to
 240 Equation 2, below. For convenience, Table 11 at the end of this document provides the resultant
 241 images per job computation for each integer product speed up through 100 ipm.

242

Equation 2: Calculation of Number of Images per Job

$$N_{IMAGES} = \begin{cases} 1 & s < 4 \\ \text{int} \left[\frac{(0.5 \times s^2)}{N_{JOBS}} \right] & s \geq 4 \end{cases}$$

243

244

Where:

245

- *N_{IMAGES}* is the number of images per job, rounded down (truncated) to the nearest integer,

246

247

- *s* is the (monochrome) maximum reported speed in images per minute (ipm), calculated in section 6.1.A, of this test procedure, and

248

249

250

- *N_{JOBS}* is the number of jobs per day, as calculated per Table 7.

251

C) Test Image: Test Pattern A from International Organization for Standardization (ISO)/IEC Standard 10561:1999 shall be used as the original image for all testing.

252

253

1) Test images shall be rendered in 10 point size in a fixed-width Courier font (or nearest equivalent).

254

255

2) German-specific characters need not be reproduced if the product is incapable of German character reproduction.

256

257

D) Print Jobs: Print jobs for the test shall be sent over the network connection designated in Table 6 immediately before printing each job.

258

259

1) Each image in a print job shall be sent separately, (i.e., all images may be part of the same document), but shall not be specified in the document as multiple copies of a single original image (unless the product is a digital duplicator).

260

261

262

2) For printers and MFDs that can interpret a page description language (PDL) (e.g., Printer Command Language PCL, Postscript), images shall be sent to the product in a PDL.

263

264

E) Copy Jobs:

265

1) For copiers with speed less than or equal to 20 ipm, there shall be one original per required image.

266

267

2) For copiers with speed greater than 20 ipm, it may not be possible to match the number of required original images (i.e., due to limits on document feeder capacity). In this case, it is permissible to make multiple copies of each original, and the number of originals shall be greater than or equal to ten.

268

269

270

271 **Example:** For a 50 ipm unit that requires 39 images per job, the test may be performed with four copies
272 of 10 originals or three copies of 13 originals.

273 3) Originals may be placed in the document feeder before the test begins.

274 a) Products without a document feeder may make all images from a single original placed on
275 the platen.

276 F) Fax Jobs: Fax jobs shall be sent via the connected phone line or line simulator immediately before
277 performing each job.

278 **Note:** DOE has included clarification that print and fax jobs shall be sent immediately before performing
279 the job because this most accurately reflects normal usage.

280 **8.2 Measurement Procedures**

281 A) Measurement of TEC shall be conducted according to Table 8 for printers, fax machines, digital
282 duplicators with print capability, and MFDs with print capability, and Table 9 for copiers, digital
283 duplicators without print capability, and MFDs without print capability, subject to the following
284 provisions:

285 1) Paper: There shall be sufficient paper in the UUT to perform the specified print or copy jobs.

286 2) Duplexing: Products shall be tested in simplex mode, unless the speed of duplex mode output is
287 greater than the speed of simplex mode output, in which case they will be tested in duplex mode.
288 In all cases, the mode in which the unit was tested and the print speed used must be
289 documented. Originals for copying shall be simplex images.

290 3) Energy Measurement Method: All measurements shall be recorded as accumulated energy over
291 time, in Wh; all time shall be recorded in minutes.

292 a) "Zero meter" references may be accomplished by recording the accumulated energy
293 consumption at that time rather than physically zeroing the meter.

Table 8: TEC Test Procedure for Printers, Fax Machines, Digital Duplicators with Print Capability, and MFDs with Print Capability

Step	Initial State	Action	Record (at end of step)	Unit of Measure	Possible States Measured
1	Off	Connect the UUT to the meter. Ensure the unit is powered and in Off Mode. Zero the meter; measure energy over 5 minutes or more. Record both energy and time.	Off energy	Watt-hours (Wh)	Off
			Testing Interval time	Minutes (min)	
2	Off	Turn on unit. Wait until unit indicates it is in Ready Mode.	–	–	–
3	Ready	Print a job of at least one output image but no more than a single job per Table 11. Measure and record time to first sheet exiting unit.	Active0 time	Minutes (min)	–
4	Ready (or other)	Wait until the meter shows that the unit has entered its final Sleep Mode or the time specified by the manufacturer.	–	–	–
5	Sleep	Zero meter; measure energy and time over 1 hour. Record the energy and time.	Sleep energy, E_{SLEEP}	Watt-hours (Wh)	Sleep
			Sleep time, t_{SLEEP} (≤ 1 hour)	Minutes (min)	
6	Sleep	Zero meter and timer. Print one job (calculated above). Measure energy and time. Record time to first sheet exiting unit. Measure energy over 15 minutes from job initiation. The job must finish within the 15 minutes.	Job1 energy, E_{JOB1}	Watt-hours (Wh)	Recovery, Active, Ready, Sleep
			Active1 time	Minutes (min)	
7	Ready (or other)	Repeat Step 6.	Job2 energy, E_{JOB2}	Watt-hours (Wh)	Same as above
			Active2 time	Minutes (min)	
8	Ready (or other)	Repeat Step 6 (without Active time measurement).	Job3 energy, E_{JOB3}	Watt-hours (Wh)	Same as above
9	Ready (or other)	Repeat Step 6 (without Active time measurement).	Job4 energy, E_{JOB4}	Watt-hours (Wh)	Same as above
10	Ready (or other)	Zero meter and timer. Measure energy and time until meter and/or unit shows that unit has entered Sleep Mode or the final Sleep Mode for units with multiple Sleep modes, or the time specified by the manufacturer, if provided. Record energy and time.	Final energy, E_{FINAL}	Watt-hours (Wh)	Ready, Sleep
			Final time, t_{FINAL}	Minutes (min)	

Table 9: TEC Test Procedure for Copiers, Digital Duplicators without Print Capability, and MFDs without Print Capability

Step	Initial State	Action	Record	Unit of Measure	Possible States Measured
1	Off	Connect the UUT to the meter. Ensure the unit is powered and in Off Mode. Zero the meter; measure energy over 5 minutes or more. Record both energy and time.	Off energy	Watt-hours (Wh)	Off
			Testing Interval time	Minutes (min)	
2	Off	Turn on unit. Wait until unit has entered Ready Mode.	–	–	–
3	Ready	Copy a job of at least one image but no more than a single job per Job Table. Measure and record time to first sheet exiting unit	Active0 time	Minutes (min)	–
4	Ready (or other)	Wait until the meter shows that the unit has entered its final Sleep Mode or the time specified by the manufacturer.	–	–	–
5	Sleep	Zero meter; measure energy and time over 1 hour or until unit enters Auto-off Mode. Record the energy and time.	Sleep energy	Watt-hours (Wh)	Sleep
			Sleep time (≤ 1 hour)	Minutes (min)	
6	Sleep	Zero meter and timer. Copy one job (calculated above). Measure and record energy and time to first sheet exiting unit. Measure energy over 15 minutes from job initiation. The job must finish within the 15 minutes.	Job1 energy, E_{JOB1}	Watt-hours (Wh)	Recovery, Active, Ready, Sleep, Auto-off
			Active1 time	Minutes (min)	
7	Ready (or other)	Repeat Step 6.	Job2 energy, E_{JOB2}	Watt-hours (Wh)	Same as above
			Active2 time	Minutes (min)	
8	Ready (or other)	Repeat Step 6 (without Active time measurement).	Job3 energy, E_{JOB3}	Watt-hours (Wh)	Same as above
9	Ready (or other)	Repeat Step 6 (without Active time measurement).	Job4 energy, E_{JOB4}	Watt-hours (Wh)	Same as above
10	Ready (or other)	Zero meter and timer. Measure energy and time until meter and/or unit shows that unit has entered its Auto-off Mode or the time specified by the manufacturer. Record energy and time; if unit began this step while in Auto-off Mode, report both energy and time values as zero.	Final energy, E_{FINAL}	Watt-hours (Wh)	Ready, Sleep
			Final time, t_{FINAL}	Minutes (min)	
11	Auto-off	Zero the meter; measure energy and time over 5 minutes or more. Record both energy and time.	Auto-off energy, E_{AUTO}	Watt-hours (Wh)	Auto-off
			Auto-off time, t_{AUTO}	Minutes (min)	

300 **9 OPERATIONAL MODE (OM) TEST PROCEDURE**

301 **9.1 Measurement Procedures**

302 A) Measurement of OM power and delay times shall be conducted according to Table 10, subject to the
303 following provisions:

304 1) Power Measurements: All power measurements shall be made using either the average power or
305 accumulated energy approaches as described below:

306 a) Average Power Method: The true average power shall be measured over the course of a
307 user selected period, which shall be no less than 10 minutes.

308

309 i) For those modes that do not last 10 minutes, the true average power shall be measured
310 over the mode's entire duration.

311 **Note:** DOE clarified how to test modes that do not last 10 minutes in order to reduce confusion during
312 testing.

313

314 b) Accumulated Energy Approach: If the test instrument is incapable of measuring the true
315 average power, the accumulated energy consumption over the course of a user selected
316 period shall be measured. The test period shall be no less than 5 minutes. The average
317 power shall be determined by dividing the accumulated energy consumption by the time of
318 the test period.

319 c) If the power consumption of the tested mode varies over a cycle then the test period shall
320 contain one or more complete cycles.

Table 10: Operational Mode (OM) Test Procedure

Step	Initial State	Action(s)	Record	Unit of Measure
1	Off	Plug the UUT into meter. Turn on unit. Wait until unit indicates it is in Ready Mode.	–	
2	Ready	Print, copy, or scan a single image.	–	
3	Ready	Measure Ready power.	Ready power, P_{READY}	Watts (W)
4	Ready	Wait and measure default delay-time to Sleep.	Sleep default-delay time, t_{SLEEP}	Minutes (min)
5	Sleep	Measure Sleep power.	Sleep power, P_{SLEEP}	Watts (W)
6	Sleep	Wait and measure default delay time to Auto-off. (Disregard if no Auto-off Mode).	Auto-off default-delay time	Minutes (min)
7	Auto-off	Measure Auto-off power. (Disregard if no Auto-off Mode).	Auto-off power $P_{AUTO-OFF}$	Watts (W)
8	Auto-off	Manually turn device off and wait until unit is off. (If no manual on-off switch, note and wait for lowest-power Sleep state).	–	–
9	Off	Measure Off power. (If no manual on-off switch, note and measure Sleep Mode power).	Off power P_{OFF}	Watts (W)

322 Notes:

- 323
- 324
- 325
- 326
- 327
- 328
- 329
- 330
- 331
- 332
- 333
- 334
- 335
- Step 1 – If the unit has no Ready indicator, use the time at which the power consumption level stabilizes to the Ready level, and note this detail when reporting the product test data.
 - Steps 4 and 5 – For products with more than one Sleep level, repeat these steps as many times as necessary to capture all successive Sleep levels and report these data. Two Sleep levels are typically used in large-format copiers and MFDs that use high-heat marking technologies. For products lacking this Mode, disregard Steps 4 and 5.
 - Steps 4 and 5 – For products without a Sleep Mode, perform and record measurements from Ready Mode.
 - Steps 4 and 6 – Default-delay time measurements are to be measured in parallel fashion, cumulative from the start of Step 4. For example, a product set to enter a Sleep level in 15 minutes and enter a second Sleep level 30 minutes after entering the first Sleep level will have a 15-minute default-delay time to the first level and a 45 minute default-delay time to the second level.

336 **10 TEST PROCEDURES FOR PRODUCTS WITH A DIGITAL FRONT**
337 **END (DFE)**

338 This step applies only to products that have a DFE as defined in Section 1 of the ENERGY STAR
339 Program Requirements for Imaging Equipment.
340

341 **Note:** DOE and EPA intend to incentivize energy efficiency of imaging products with DFEs by measuring
342 the energy consumption of the DFE in the modes that are most prevalent: Ready and Sleep. This change
343 will require retesting of all imaging equipment units with DFEs.

344
345 Following retesting, the energy savings potential of DFE energy consumption requirements will be
346 analyzed and DFE energy consumption requirements may be proposed for discussion during the
347 specification development process.

348 **10.1 DFE Testing**

349 A) If the DFE has a separate main power cord, regardless of whether the cord and controller are
350 internal or external to the imaging product, a 10 minute energy measurement of the DFE alone
351 shall be made while the main product is in Ready Mode. The unit must be connected to a
352 network if applicable.

353 B) If the DFE does not have a separate main power cord, the manufacturer shall measure the dc
354 power required for the DFE when the unit as a whole is in Ready Mode. This will most commonly
355 be accomplished by taking an instantaneous power measurement of the dc input to the DFE.

356
357 **Note:** DOE and EPA are proposing to require that manufacturers directly report the dc power to the DFE
358 without adjusting for any power supply inefficiency as such adjustments are likely to be unreliable without
359 knowing the efficiency curve of the power supply used for the test.

360
361 C) If the DFE has a Sleep Mode that is enabled as-shipped, wait until the DFE is in a Sleep Mode
362 and repeat one of the above measurements, as appropriate for the DFE type, recording the DFE
363 Sleep Mode power.

- 364 1) Manufacturers shall provide information on:
365 a) Whether DFE Sleep Mode is enabled as-shipped; and
366 b) The expected time to sleep of the DFE.
367 2) If no Sleep Mode is enabled as-shipped, the Ready Mode value measured in Section A)
368 or B), above, shall be recorded as the DFE Sleep Mode power.

369
370 **Note:** DOE and EPA are considering incentives to encourage implementation of ProxZzy technology
371 during sleep mode in DFE products. We welcome stakeholder input as to the best methods to incentivize
372 this technology.

373 **11 REFERENCES**

374 A) ISO/IEC 10561:1999. Information technology — Office equipment — Printing devices — Method
375 for measuring throughput — Class 1 and Class 2 printers.

376 B) IEC 62301:2011 . Household Electrical Appliances – Measurement of Standby Power. Ed. 2.0.

Table 11: Number of Images per Day Calculated for Product Speeds from 1 to 100 ipm

Speed (ipm)	Jobs/Day	Unrounded Images/ Job	Images/ Job	Images/ Day	Speed (ipm)	Jobs/Day	Unrounded Images/ Job	Images/ Job	Images/ Day
1	8	0.06	1	8	51	32	40.64	40	1280
2	8	0.25	1	8	52	32	42.25	42	1344
3	8	0.56	1	8	53	32	43.89	43	1376
4	8	1.00	1	8	54	32	45.56	45	1440
5	8	1.56	1	8	55	32	47.27	47	1504
6	8	2.25	2	16	56	32	49.00	49	1568
7	8	3.06	3	24	57	32	50.77	50	1600
8	8	4.00	4	32	58	32	52.56	52	1664
9	9	4.50	4	36	59	32	54.39	54	1728
10	10	5.00	5	50	60	32	56.25	56	1792
11	11	5.50	5	55	61	32	58.14	58	1856
12	12	6.00	6	72	62	32	60.06	60	1920
13	13	6.50	6	78	63	32	62.02	62	1984
14	14	7.00	7	98	64	32	64.00	64	2048
15	15	7.50	7	105	65	32	66.02	66	2112
16	16	8.00	8	128	66	32	68.06	68	2176
17	17	8.50	8	136	67	32	70.14	70	2240
18	18	9.00	9	162	68	32	72.25	72	2304
19	19	9.50	9	171	69	32	74.39	74	2368
20	20	10.00	10	200	70	32	76.56	76	2432
21	21	10.50	10	210	71	32	78.77	78	2496
22	22	11.00	11	242	72	32	81.00	81	2592
23	23	11.50	11	253	73	32	83.27	83	2656
24	24	12.00	12	288	74	32	85.56	85	2720
25	25	12.50	12	300	75	32	87.89	87	2784
26	26	13.00	13	338	76	32	90.25	90	2880
27	27	13.50	13	351	77	32	92.64	92	2944
28	28	14.00	14	392	78	32	95.06	95	3040
29	29	14.50	14	406	79	32	97.52	97	3104
30	30	15.00	15	450	80	32	100.00	100	3200
31	31	15.50	15	465	81	32	102.52	102	3264
32	32	16.00	16	512	82	32	105.06	105	3360
33	32	17.02	17	544	83	32	107.64	107	3424
34	32	18.06	18	576	84	32	110.25	110	3520
35	32	19.14	19	608	85	32	112.89	112	3584
36	32	20.25	20	640	86	32	115.56	115	3680
37	32	21.39	21	672	87	32	118.27	118	3776
38	32	22.56	22	704	88	32	121.00	121	3872
39	32	23.77	23	736	89	32	123.77	123	3936
40	32	25.00	25	800	90	32	126.56	126	4032
41	32	26.27	26	832	91	32	129.39	129	4128
42	32	27.56	27	864	92	32	132.25	132	4224
43	32	28.89	28	896	93	32	135.14	135	4320
44	32	30.25	30	960	94	32	138.06	138	4416
45	32	31.64	31	992	95	32	141.02	141	4512
46	32	33.06	33	1056	96	32	144.00	144	4608
47	32	34.52	34	1088	97	32	147.02	147	4704
48	32	36.00	36	1152	98	32	150.06	150	4800
49	32	37.52	37	1184	99	32	153.14	153	4896
50	32	39.06	39	1248	100	32	156.25	156	4992