

Idle Energy Data: Stationary Rack Door Type Machines				
Data Point	High Temp or Low Temp	Minimum Tank Temperature During Idle Test	Average Tank Temperature During Idle Test	Tank Heater Idle Energy Rate Door Closed (kW)
1	High	159.7° F	161.7° F	0.60
2	High	150° F	154° F	0.33
3	High	165° F	167.1° F	0.70
4	High	150° F	156° F	0.90
5	High	153.2° F	155.8° F	0.53
6	High	153.2° F	155.8° F	0.53
7	High	153.2° F	155.8° F	0.53
8	High	153.2° F	155.8° F	0.53
9	High	153.2° F	155.8° F	0.53
10	High	152° F	154° F	0.65
11	Low	130.1° F	132.5° F	0.33
12	Low	130.1° F	132.5° F	0.33
13	Low	130.1° F	132.5° F	0.33
14	Low	130.1° F	132.5° F	0.33
15	Low	130.1° F	132.5° F	0.33
16	Low	N/A	N/A	0.00
17	Low	N/A	N/A	0.00
18	Low	N/A	N/A	0.00
19	Low	N/A	N/A	0.00
20	Low	N/A	N/A	0.00
21	Low	N/A	N/A	0.00
22	Low	N/A	N/A	0.00
23	Low	N/A	N/A	0.00
24	Low	N/A	N/A	0.00

Number of Manufacturers = 7