



# ENERGY STAR<sup>®</sup> Program Requirements for Products with Battery Charging Systems (BCSs)

## Partner Commitments

### Commitment

The following are the terms of the ENERGY STAR Partnership Agreement as it pertains to ENERGY STAR qualified battery charging systems (BCS) packaged with a variety of end-use products. The ENERGY STAR Partner must adhere to the following program requirements:

- comply with current ENERGY STAR Eligibility Criteria for BCSs, as follows: To be eligible for the ENERGY STAR program, the BCS packaged with an end-use product must be an ENERGY STAR qualified BCS. EPA may, at its discretion, conduct market research or tests on products that are referred to as containing an ENERGY STAR qualified BCS. These products may be obtained on the open market, or voluntarily supplied by Partner at EPA's request;
- comply with current ENERGY STAR Identity Guidelines, describing how the ENERGY STAR marks and name may be used. Partner is responsible for adhering to these guidelines, which include instructions for using the ENERGY STAR BCS graphic that was specifically developed for BCS Partners, and for ensuring that its authorized representatives, such as advertising agencies, dealers, and distributors, are also in compliance;
- qualify at least one BCS within three months of activating the BCS portion of the agreement. When Partner qualifies the product, it must meet the specification (e.g., Tier 1 or 2) in effect at that time;
- provide clear and consistent labeling of materials for end-use products with qualified BCSs. The ENERGY STAR BCS graphic must be clearly displayed:
  1. on the manufacturer's Internet site where information about end-use products with ENERGY STAR qualified BCSs is provided, and
  2. *either* on the external product packaging (preferably the front face, outside of the box), *or* on an insert within the box/packaging, *or* in another creative application provided that a plan is submitted to EPA for consideration and approved prior to implementation.

Partner is also encouraged to use the BCS graphic in product literature (e.g., user manuals) and product advertising/promotional materials. **Partner is prohibited from directly affixing the BCS graphic to the end-use product or the battery charger.** However, it may be displayed on a cord tag that is fastened to a BCS cord;

- provide to EPA, on a semi-annual basis, an updated list of ENERGY STAR qualified BCSs and their associated end-use products. Once the Partner submits its first list of ENERGY STAR qualified BCSs, the Partner will be listed as an ENERGY STAR Partner on the ENERGY STAR Web site and in other materials. Partner must provide semi-annual updates in order to remain on the list of participating product manufacturers;
- provide to EPA, on an annual basis, unit shipment data or other market indicators to assist in determining the market penetration of ENERGY STAR qualified BCSs and their associated end-use products. Specifically, Partner must submit the total number of ENERGY STAR qualified BCSs shipped (in units by model) or an equivalent measurement as agreed to in advance by EPA and Partner. Partner is also encouraged to provide ENERGY STAR qualified unit shipment data segmented by meaningful product characteristics (e.g., capacity, size, speed, or other as relevant), total unit shipments for each model in its product line, and percent of total unit shipments that use an ENERGY STAR qualified BCS. The data for each calendar year should be submitted to EPA, preferably in electronic format, no later than the following March and may be provided directly from the Partner or through a third party. The data will be used by EPA only for program evaluation purposes and will be closely controlled. Any information used will be masked by EPA so as to protect the confidentiality of the Partner;

- notify EPA of a change in the designated responsible party or contacts for BCSs within 30 days.

## **Performance for Special Distinction**

In order to receive additional recognition and/or support from EPA for its efforts within the Partnership, the ENERGY STAR Partner may consider the following voluntary measures and should keep EPA informed on the progress of these efforts:

- specify ENERGY STAR qualified BCSs across all applicable product types;
- consider energy efficiency improvements in company facilities and pursue the ENERGY STAR label for buildings;
- purchase ENERGY STAR qualified products. Revise the company purchasing or procurement specifications to include ENERGY STAR. Provide procurement officials' contact information to EPA for periodic updates and coordination. Circulate general ENERGY STAR qualified product information to employees for use when purchasing products for their homes;
- ensure the power management feature is enabled on all ENERGY STAR qualified computer monitors in use in company facilities, particularly upon installation and after service is performed;
- provide general information about the ENERGY STAR program to employees whose jobs are relevant to the development, marketing, sales, and service of current end-use products with ENERGY STAR qualified BCSs;
- feature the ENERGY STAR mark(s) on Partner Web site and in other promotional materials. If information concerning ENERGY STAR is provided on the Partner Web site as specified by the ENERGY STAR Web Linking Policy (this document can be found in the Partner Resources section on the ENERGY STAR Web site at [www.energystar.gov](http://www.energystar.gov)), EPA may provide links where appropriate to the Partner Web site.
- provide a simple plan to EPA outlining specific measures Partner plans to undertake beyond the program requirements listed above. By doing so, EPA may be able to coordinate, communicate, and/or promote Partner's activities, provide an EPA representative, or include news about the event in the ENERGY STAR newsletter, on the ENERGY STAR Web pages, etc. The plan may be as simple as providing a list of planned activities or planned milestones that Partner would like EPA to be aware of. For example, activities may include: (1) increase the availability of ENERGY STAR qualified products by converting the entire product line within two years to meet ENERGY STAR guidelines; (2) demonstrate the economic and environmental benefits of energy efficiency through special in-store displays twice a year; (3) provide information to users (via the Web site and user's manual) about energy-saving features and operating characteristics of ENERGY STAR qualified products, and (4) build awareness of the ENERGY STAR Partnership and brand identity by collaborating with EPA on one print advertorial and one live press event;
- provide quarterly, written updates to EPA as to the efforts undertaken by Partner to increase availability of ENERGY STAR qualified products, and to promote awareness of ENERGY STAR and its message.



# ENERGY STAR® Program Requirements for Products with Battery Charging Systems (BCSs)

## Eligibility Criteria

---

### Table of Contents

Section 1: Definitions	2
Section 2: Qualifying Products	4
Section 3: Energy Performance Specifications for Qualifying Products	5
Table 1: Energy Performance Criteria for Common Battery Voltages	5
Section 4: Test Methodology	5
Section 5: Effective Date	6
Section 6: Future Specification Revisions	6



# ENERGY STAR® Program Requirements for Products with Battery Charging Systems (BCSs)

## Eligibility Criteria

Below is the specification for ENERGY STAR qualified battery charging systems. Battery charging systems consist of the combination of a battery charger and battery as defined below. Covered systems may be either a battery charger with a detachable battery pack or a battery charger system functioning with a product or appliance that is powered by an integral battery. A battery charging system must meet all of the identified criteria if it is to be qualified as ENERGY STAR by its manufacturer.

While addressing a different set of product designs, this specification is intended to complement the existing ENERGY STAR external power supply specification. Manufacturers shall carefully examine their product designs and compare them to the detailed definitions (Section 1) and qualifying product descriptions (Section 2) for a battery charging system and external power supply (visit [www.energystar.gov/powersupplies](http://www.energystar.gov/powersupplies)) to determine the appropriate specification for ENERGY STAR qualification. Manufacturers may only qualify individual models under the one specification (i.e., external power supply OR battery charging system) that best reflects the power supply and product design. Note that a qualified battery charging system may use an ENERGY STAR qualified external power supply, but this is not sufficient or necessary to qualify the battery charging system as ENERGY STAR.

- 1) **Definitions:** Below are detailed definitions of battery charging systems and other related terms as relevant to ENERGY STAR.

### **General**

- A. **Battery (also Battery Pack):** An assembly of one or more rechargeable cells intended to provide electrical energy to an end-use product. Rechargeable cells are any of a number of established cell chemistries intended for repetitive charge/discharge cycles. Primary alkaline cells are not considered rechargeable. Batteries may be in one of the following forms:
  - a) **Detachable Battery:** A battery that is contained in a separate enclosure from the end-use product and is intended to be removed or disconnected from the end-use product for recharging.
  - b) **Integral Battery:** A battery that is contained within the end-use product and is not removed from the end-use product for charging purposes. A battery that is to be removed from the end-use product for disposal or recycling purposes only is considered to be an integral battery.
- B. **Battery Charger:** A device intended to replenish the charge in a rechargeable battery. The battery charger will connect to the mains at the power input and connect to the battery at the output. The charger may be comprised of multiple components, in more than one enclosure, and may be all or partially contained in the end-use product.
  - a) **A La Carte Charger:** A separable battery charger that is individually packaged without batteries. Batteries that the a la carte charger is designed to charge should be listed on the packaging, battery, and/or in the user materials.
  - b) **Multi-Voltage Charger:** A battery charger that, by design, may charge a variety of batteries that are of different nominal voltages.
  - c) **Multi-Port Charger:** A battery charger that, by design, is capable of simultaneously charging two or more batteries. These chargers also may have multi-voltage capability, allowing two or more batteries of different voltages to charge simultaneously or sequentially.
  - d) **Stand-Alone Charger:** A battery charger that, by design, charges separable batteries disconnected from the end-use product.
  - e) **Batch Charger:** With some multi-port chargers, such as universal AA battery chargers, single cells are charged in batches (i.e., groups of batteries charged in series). For the purposes of this specification, each of these batches shall be treated as a discrete battery pack. For example, a AA Nickel Metal Hydride charger with four ports may charge in two

batches, with the batches connected in parallel. Each batch, in this case, would be treated as a single 2.4V battery pack. Charging four AA batteries in this system would be considered, for the purposes of this specification, as a multi-port charger charging two 2.4V batteries in parallel.

- C. Battery Charging System: A combination of battery charger and battery, detachable or integral, which is intended to power a cordless product.

#### **Device Types**

- D. Battery Operated End-use Product: Product or appliance fully powered by the battery at least part of the time.
- E. Cord/Cordless: Product or appliance that is designed to run on battery power, but also is designed such that the product or appliance can run with a discharged battery when connected to the mains.
- F. Inductive Coupling: A system in which power is transferred between windings in two *separate enclosures* through magnetic induction rather than metal-to-metal contact. This design limits the possibility of electric shock or a short circuit and is often used in certain small household appliances, such as cordless toothbrushes and shavers.

#### **Operational Modes**

- G. Active Mode: The condition in which the battery is receiving the main charge, equalizing cells, and performing other one-time or limited-time functions necessary for bringing the battery to the fully charged state.
- H. Battery Maintenance Mode: The condition in which the battery is still connected to the charger, but has been fully charged. This mode may persist for an indefinite period of time.
- I. Standby (No-Load) Mode: Lowest power consumption mode which cannot be switched off (influenced) by the user and that may persist for an indefinite time when an appliance is connected to the main electricity supply and used in accordance with the manufacturer's instructions. Note: The standby mode is usually a non-operational mode when compared to the intended use of the appliance's primary function.<sup>1</sup> For the purposes of this specification, standby mode is the condition in which no battery is present in the charger, or where the battery is integral to a product, the product is not attached to the charger, but the charger is plugged in and drawing power.

#### **Test/Measurement Terminology**

- J. Accumulated Nonactive Energy (E<sub>a</sub>): The energy, in watt-hours (Wh), consumed by the battery charger in battery maintenance and standby modes of operation over a defined period. For the purposes of this specification, the 48-hour period consists of 36 hours of maintenance mode operation followed by 12 hours of standby mode operation. The accumulated nonactive energy is the sum of the energy used in these two modes.
- K. Battery Capacity: The quantity of charge, measured in ampere-hours (Ah), capable of being provided by a battery during discharge, the conditions of discharge being specified.
- L. Battery Energy (E<sub>b</sub>): The energy, in watt-hours (Wh), deliverable by the battery under known discharge conditions. For the purposes of this specification and test methodology, the battery energy shall be measured at a constant current discharge rate of 0.2 C. The test shall begin with a fully charged battery, which is then discharged until the battery reaches its manufacturer specified cutoff voltage. The battery energy is determined by measuring and integrating the battery voltage over the course of discharge and multiplying by the constant current load. This value shall be reported by the manufacturer and is subject to verification by EPA.

---

<sup>1</sup> This definition is consistent with IEC 62301: Household Electrical Appliances – Measurement of Standby Power.

- M. **Nameplate Input Power:** The nameplate input power is either 1) the input power marked on the nameplate (watts), or 2) where only nameplate input voltage and current ranges are provided, the highest value achieved by multiplying a nameplate input voltage limit and its corresponding current limit (Volt-Amperes).
- N. **Nominal Battery Voltage (Vb):** Industry standard cell voltage multiplied by the number of cells in the battery pack, normally listed on battery packaging. As of the writing of this battery charging systems specification, industry accepted nominal cell voltages for applicable chemistries include: 1.2 volts for Nickel Cadmium and Nickel Metal Hydride; 2.0 volts for sealed lead acid; and 2.5-4.2 volts for Lithium Ion (depending on material used for the positive electrode and other factors).
- O. **Nonactive Energy Ratio (ER):** The ratio of the accumulated nonactive energy (Ea) divided by the battery energy (Eb).  $ER = Ea / Eb$ .

2) **Qualifying Products:** This ENERGY STAR specification applies to:

- a) Battery charging systems packaged with portable, rechargeable products whose principal output is mechanical motion, light, the movement of air, or the production of heat (e.g., small home appliances, personal care products, power tools, flashlights, and floor care products);
- b) Stand-alone battery chargers sold with products that use a detachable battery (e.g., some digital camera and camcorder designs); and
- c) Battery charging systems intended to replace standard sized primary alkaline cells including: AAA, AA, C, D, 9-volt, etc. (i.e., universal battery chargers).

In addition, battery charging systems must meet the following conditions:

1. Chargers must be intended for rechargeable battery chemistries (e.g., Nickel Cadmium, Lead Acid, Lithium Ion, and Nickel Metal Hydride) and not for primary cell chemistries (e.g., alkaline “dry” cells);
2. Chargers may not rely on an inductive coupling system used to transfer energy between two separate enclosures;
3. Batteries must have voltages less than 42 volts;
4. Chargers must have nameplate input power between 2 and 300 watts;
5. Chargers may not have a secondary functionality that draws power while the battery is being charged/maintained (e.g., radio, cleaning machine, etc.) and is not related to charging, maintaining, or monitoring a battery. These systems may, however, draw power to provide a simple clock function and/or state of charge indicator. This exclusion does not apply to 1) battery charging systems that provide power from the mains to operate cord/cordless products or appliances with a discharged battery, and 2) products containing additional functions that do not draw additional power;
6. All products must meet the ENERGY STAR requirements as packaged for sale. A la carte chargers, which also may be multi-voltage and/or multi-port, may qualify as ENERGY STAR if they meet the requirements when tested using at least three currently produced batteries identified/listed as usable with the unit, as required in the ENERGY STAR Test Methodology.<sup>2</sup> If the same a la carte battery charger model also is packaged for sale with end-use products using batteries, these systems may only qualify if the specific charger and battery combinations also meet the ENERGY STAR requirements; and
7. Multi-port chargers may qualify if they meet the ENERGY STAR requirements when tested with multiple identical batteries as outlined in the ENERGY STAR Test Methodology. Similarly, multi-voltage chargers may qualify if they meet the ENERGY STAR requirements with all applicable batteries of differing voltages as outlined in the ENERGY STAR Test Methodology.

The following types of battery charging systems are not covered by this ENERGY STAR specification:

1. Inductively coupled devices used to transfer energy between two separate enclosures;
2. Chargers with nameplate input power less than 2 watts and greater than 300 watts; and
3. Charging systems that draw additional power to support added functionality such as radios, CD players, GFI AC outlets, and cleaning devices.

<sup>2</sup> See Section 4 for “Test Method for Determining the Energy Performance of Battery Charging Systems (Final, December 2005).”

In order to qualify as ENERGY STAR, a model must meet the above parameters and the energy performance criteria provided in Section 3, below.

Please note that single voltage external power supplies (including some that use the power supply's dc output to charge batteries) and the end-use products they power are covered under separate ENERGY STAR agreements (“ENERGY STAR Program Requirements for Single Voltage External Ac-Dc and Ac-Ac Power Supplies” and “ENERGY STAR Program Requirements for End-Use Products Using External Power Supplies”). Visit [www.energystar.gov/powersupplies](http://www.energystar.gov/powersupplies) for additional information.

- 3) **Energy Performance Specifications for Qualifying Products:** To be eligible for ENERGY STAR qualification, a battery charging system must not exceed a maximum Nonactive Energy Ratio, which is based on the nominal battery voltage (Vb). The maximum allowed Nonactive Energy Ratios are provided in Table 1 below for select battery voltages. For intermediate voltages, the battery charging system must not exceed the maximum Energy Ratio associated with the next highest voltage represented in the table. (Example: A product using a battery with a nominal voltage of 14.0 volts would need to meet a maximum Energy Ratio of 4.5, consistent with the requirements for the next highest voltage of 14.4 volts, to qualify as ENERGY STAR.)

**Table 1: Energy Performance Criteria for Common Battery Voltages**

<b>Vb</b>	<b>1.2</b>	<b>2.4</b>	<b>3.6</b>	<b>4.8</b>	<b>6.0</b>	<b>7.2</b>	<b>8.4</b>	<b>9.6</b>	<b>10.8</b>	<b>12.0</b>
<b>ER</b>	20.0	16.9	13.7	11.6	9.6	7.5	7.0	6.5	6.1	5.6
<b>Vb</b>	<b>13.2</b>	<b>14.4</b>	<b>15.6</b>	<b>16.8</b>	<b>18.0</b>	<b>19.2</b>	<b>20.4</b>	<b>21.6</b>	<b>22.8</b>	<b>≥ 24.0</b>
<b>ER</b>	5.1	4.5	4.3	4.2	3.8	3.6	3.5	3.3	3.2	3.0

Given that multi-voltage and multi-port chargers require testing more than one battery pack, their Nonactive Energy Ratios must be calculated differently. For these chargers, the Nonactive Energy Ratio is calculated by taking the total accumulated energy from all tests and dividing by the sum of all the tested battery capacities. The reference voltage used to identify the maximum allowable Nonactive Energy Ratio is determined by averaging the battery voltages of all batteries tested. For single-voltage, multi-port chargers, this calculation method leads to taking the total accumulated energy from charging identical batteries and dividing by the sum of their capacities. The nominal voltage of a single identical battery pack is then used to identify the maximum allowable Nonactive Energy Ratio. For chargers that charge individual cells in batches, the Nonactive Energy Ratio is calculated by taking the total accumulated energy from all tests and dividing by the sum of all the tested battery capacities. The reference voltage used to identify the maximum allowable Nonactive Energy Ratio is the arithmetic mean of all of the batch voltages tested. Please refer to the ENERGY STAR Test Methodology for additional details.

- 4) **Test Methodology:** The specifics for testing the energy performance of a battery charging system are outlined in a separate document titled “Test Methodology for Determining the Energy Performance of Battery Charging Systems (Final, December 2005),” which is available on the ENERGY STAR Web site. The test results produced by this procedure shall be used to determine if a model qualifies as ENERGY STAR. In addition, below are four ENERGY STAR-specific testing requirements.
- A. **Safety Standards:** ENERGY STAR qualified battery charging systems shall comply with applicable local product safety requirements in the market(s) in which the product is to be sold. It is the Partner’s responsibility to ensure that its products meet acceptable standards of safety for battery charging systems.

- B. **Number of Units Required for Test:** Testing shall be conducted by the manufacturer or its authorized representative on three randomly chosen units of the same model. Manufacturers shall report Energy Ratio values for all three units as well as the average values. To qualify as ENERGY STAR, all three units must meet the ENERGY STAR specification; however, the average of the three test values will be displayed on ENERGY STAR's qualifying product list (see Section 4.D below).
- C. **Models Capable of Operating at Multiple Voltage/Frequency Combinations:** Manufacturers shall test their products based on the market(s) in which the models will be sold and promoted as ENERGY STAR qualified. EPA and its ENERGY STAR Country Partners have developed the following table with three voltage/frequency combinations for testing purposes:

<b>Supply Voltage:</b>	North America/Taiwan:	115 volts ac, 60 Hz
	Europe/Australia/New Zealand:	230 volts ac, 50 Hz
	Japan:	100 Volts AC, 50 Hz or 60 Hz (either frequency is acceptable)

For products that are sold as ENERGY STAR in multiple international markets and therefore rated at multiple input voltages, the manufacturer must test at and report the required power consumption, energy performance, or efficiency values at all relevant voltage/frequency combinations. For example, a manufacturer that is shipping the same model to the United States and Europe must measure, meet the specification, and report test values at both 115 volts, 60 Hz and 230 volts, 50 Hz in order to qualify the model as ENERGY STAR in both markets. If a model qualifies as ENERGY STAR at only one voltage/frequency combination (e.g., 115 volts, 60 Hz), then it may only be qualified and promoted as ENERGY STAR in those regions that support the tested voltage/frequency combination (e.g., North America and Taiwan).

- D. **Submission of Qualified Product Data to EPA:** Partners are required to self-certify those product models that meet the ENERGY STAR guidelines and report information to EPA. ENERGY STAR qualifying product lists, including new models as well as notification of discontinued models, must be provided at least semi-annually. If no new models are introduced during a six-month timeframe, manufacturer should notify EPA to ensure its partnership status is maintained.
- 5) **Effective Date:** The date that manufacturers may begin to qualify and promote battery charging systems as ENERGY STAR will be defined as the *effective date* of the agreement. The ENERGY STAR battery charging systems effective date is January 1, 2006.
- 6) **Future Specification Revisions:** EPA reserves the right to change the specification should technological and/or market changes affect its usefulness to consumers, industry, or the environment. In keeping with current policy, revisions to the specification are arrived at through stakeholder discussions. In the event of a specification revision, please note that ENERGY STAR qualification is not automatically granted for the life of a product model. To qualify as ENERGY STAR, a product model must meet the ENERGY STAR specification in effect on the model's date of manufacture. The date of manufacture is specific to each unit and is the date on which a unit is considered to be completely assembled.